

Java Server Faces

Table of contents

1 Introduction.....	2
2 Enabling Java Server Faces.....	2
2.1 Integrate JSF Tags in Your Web App.....	2
2.2 Configure Your Web Application.....	2

1. Introduction

[JavaServer Faces](http://java.sun.com/j2ee/javaserverfaces/) (<http://java.sun.com/j2ee/javaserverfaces/>) is technology for building web application user interfaces. It allows development of very rich component- and event-based pages. Page Flow treats JSF pages as *first-class citizens*. In addition to allowing the use of "straight" JSF features, it integrates in the following ways:

- When a JSF page is hit, either directly or from a Page Flow action, an associated "backing bean" class is looked up. If it exists, an instance is created and managed by the framework. This bean can contain JSF component references, event handlers, etc., and it can *raise Page Flow actions*, with or without form beans attached. Its lifetime is tied to the lifetime of the JSF page.
- Components in JSF pages can also raise Page Flow actions directly, with or without form beans attached, using the built-in `action` attribute.
- Pages can databind to Page Flow objects using JSF-style expressions like `{pageFlow.someProperty}` or `{pageInput.somePageInput.someProperty}`.
- A page can databind to properties in its associated backing bean through a "backing" context, e.g., `{backing.someProperty}`.
- When returning to a JSF page through the [navigateTo](#) ([./apidocs/classref_pageflows/org/apache/beehive/netui/pageflow/annotations/Jpf.Forward.html#navigateTo](http://apidocs.classref_pageflows/org/apache/beehive/netui/pageflow/annotations/Jpf.Forward.html#navigateTo)) feature, the page's component tree and its backing bean are restored.

The [Page Flow / JSF Sample](#) ([sample_jpf_jsf_integration.html](#)) demonstrates these features.

2. Enabling Java Server Faces

To enable Java Server Faces in a Beehive web application, complete the following steps:

2.1. Integrate JSF Tags in Your Web App

Integrate JSF into your webapp. You can use either [MyFaces v1.0.9 or later](#) (<http://myfaces.apache.org>) , or the [JSF Reference Implementation v1.1_01](#) (<http://java.sun.com/j2ee/javaserverfaces/download.html>) .

2.2. Configure Your Web Application

Add the following snippet to your `WEB-INF/faces-config.xml` file:

```
<factory>
  <application-factory>
    org.apache.beehive.netui.pageflow.faces.PageFlowApplicationFactory
  </application-factory>
```

Java Server Faces

```
</factory>
```

This goes underneath the `<application>` element and before the `<navigation-rule>` element(s).

Java, J2EE, and JCP are trademarks or registered trademarks of Sun Microsystems, Inc. in the United States and other countries.

© 2004, Apache Software Foundation