

Cayenne Guide

Version 4.0 (4.0.RC1)

Table of Contents

1. Object Relational Mapping with Cayenne	2
1.1. Setup	2
1.2. Cayenne Mapping Structure	3
1.3. CayenneModeler Application	5
2. Cayenne Framework	7
2.1. Including Cayenne in a Project	7
2.2. Starting Cayenne	19
2.3. Persistent Objects andObjectContext	22
2.4. Expressions	29
2.5. Orderings	35
2.6. Queries	35
2.7. Lifecycle Events	53
2.8. Performance Tuning	59
2.9. Customizing Cayenne Runtime	66
3. Cayenne Framework - Remote Object Persistence	77
3.1. Introduction to ROP	77
3.2. ROP Deployment	78
4. DB-First Flow	79
4.1. Introduction	79
4.2. Filtering	80
4.3. Other Settings	87
4.4. Reverse Engineering in Cayenne Modeler	88
5. Cayenne Additional Modules	91
5.1. Cache invalidation extension	91
5.2. Commit log extension	92
5.3. Crypto extension	93
5.4. Apache Commons DBCP integration	95
5.5. Java 8 extension	96
5.6. JCache integration	97
5.7. Joda time extension	98
6. Appendix A. Configuration Properties	99
7. Appendix B. Service Collections	102
8. Appendix C. Expressions BNF	104
9. List of tables	107

License

Licensed to the Apache Software Foundation (ASF) under one or more contributor license agreements. See the NOTICE file distributed with this work for additional information regarding copyright ownership. The ASF licenses this file to you under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at <http://www.apache.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

Chapter 1. Object Relational Mapping with Cayenne

1.1. Setup

System Requirements

- **Java:** Cayenne runtime framework and CayenneModeler GUI tool are written in 100% Java, and run on any Java-compatible platform. Minimal required JDK version depends on the version of Cayenne you are using, as shown in the following table:

Table 1. Cayenne Version History

Cayenne Version	Java Version	Status
4.1	Java 1.8 or newer	Development
4.0	Java 1.7 or newer	Beta
3.1	Java 1.5 or newer	Stable
3.0	Java 1.5	Aging
1.2 / 2.0	Java 1.4	Legacy
1.1	Java 1.3	Legacy

- **JDBC Driver:** An appropriate DB-specific JDBC driver is needed to access the database. It can be included in the application or used in web container DataSource configuration.
- **Third-party Libraries:** Cayenne runtime framework has a minimal set of required and a few more optional dependencies on third-party open source packages. See [Including Cayenne in a Project](#) chapter for details.

Running CayenneModeler

CayenneModeler GUI tool is intended to work with object relational mapping projects. While you can edit your XML by hand, it is rarely needed, as the Modeler is a pretty advanced tool included in Cayenne distribution. To obtain CayenneModeler, download Cayenne distribution archive from <http://cayenne.apache.org/download.html> matching the OS you are using. Of course Java needs to be installed on the machine where you are going to run the Modeler.

- OS X distribution contains CayenneModeler.app at the root of the distribution disk image.
- Windows distribution contains CayenneModeler.exe file in the bin directory.
- Cross-platform distribution (targeting Linux, but as the name implies, compatible with any OS) contains a runnable CayenneModeler.jar in the bin directory. It can be executed either by double-clicking, or if the environment is not configured to execute jars, by running from command-line:

```
$ java -jar CayenneModeler.jar
```

The Modeler can also be started from Maven. While it may look like an exotic way to start a GUI application, it has its benefits - no need to download Cayenne distribution, the version of the Modeler always matches the version of the framework, the plugin can find mapping files in the project automatically. So it is an attractive option to some developers. Maven option requires a declaration in the POM:

```
<build>
  <plugins>
    <plugin>
      <groupId>org.apache.cayenne.plugins</groupId>
      <artifactId>cayenne-modeler-maven-plugin</artifactId>
      <version>4.0.RC1</version>
    </plugin>
  </plugins>
</build>
```

And then can be run as

```
$ mvn cayenne-modeler:run
```

Table 2. Modeler plugin parameters

Name	Type	Description
modelFile	File	<p>Name of the model file to open. Here is some simple example:</p> <pre><plugin> <groupId>org.apache.cayenne.plugins</groupId> <artifactId>cayenne-modeler-maven- plugin</artifactId> <version>\${cayenne.version}</version> <configuration> <modelFile> src/main/resources/cayenne.xml</modelFile> </configuration> </plugin></pre>

1.2. Cayenne Mapping Structure

Cayenne Project

A Cayenne project is an XML representation of a model connecting database schema with Java classes. A project is normally created and manipulated via CayenneModeler GUI and then used to initialize Cayenne runtime. A project is made of one or more files. There's always a root project descriptor file in any valid project. It is normally called cayenne-xyz.xml, where "xyz" is the name of the project.

Project descriptor can reference DataMap files, one per DataMap. DataMap files are normally called xyz.map.xml, where "xyz" is the name of the DataMap. For legacy reasons this naming convention is different from the convention for the root project descriptor above, and we may align it in the future versions. Here is how a typical project might look on the file system:

```
$ ls -l
total 24
-rw-r--r--  1 cayenne  staff  491 Jan 28 18:25 cayenne-project.xml
-rw-r--r--  1 cayenne  staff  313 Jan 28 18:25 datamap.map.xml
```

DataMap are referenced by name in the root descriptor:

```
<map name="datamap"/>
```

Map files are resolved by Cayenne by appending ".map.xml" extension to the map name, and resolving the resulting string relative to the root descriptor URI. The following sections discuss various ORM model objects, without regards to their XML representation. XML format details are really unimportant to the Cayenne users.

DataMap

DataMap is a container of persistent entities and other object-relational metadata. DataMap provides developers with a scope to organize their entities, but it does not provide a namespace for entities. In fact all DataMaps present in runtime are combined in a single namespace. Each DataMap must be associated with a DataNode. This is how Cayenne knows which database to use when running a query.

DataNode

DataNode is model of a database. It is actually pretty simple. It has an arbitrary user-provided name and information needed to create or locate a JDBC DataSource. Most projects only have one DataNode, though there may be any number of nodes if needed.

DbEntity

DbEntity is a model of a single DB table or view. DbEntity is made of DbAttributes that correspond to columns, and DbRelationships that map PK/FK pairs. DbRelationships are not strictly tied to FK constraints in DB, and should be mapped for all logical "relationships" between the tables.

ObjEntity

ObjEntity is a model of a single persistent Java class. ObjEntity is made of ObjAttributes and ObjRelationships. Both correspond to entity class properties. However ObjAttributes represent "simple" properties (normally things like String, numbers, dates, etc.), while ObjRelationships correspond to properties that have a type of another entity.

ObjEntity maps to one or more DbEntities. There's always one "root" DbEntity for each ObjEntity.

ObjAttribute maps to a DbAttribute or an Embeddable. Most often mapped DbAttribute is from the root DbEntity. Sometimes mapping is done to a DbAttribute from another DbEntity somehow related to the root DbEntity. Such ObjAttribute is called "flattened". Similarly ObjRelationship maps either to a single DbRelationship, or to a chain of DbRelationships ("flattened" ObjRelationship).

ObjEntities may also contain mapping of their lifecycle callback methods.

Embeddable

Embeddable is a model of a Java class that acts as a single attribute of an ObjEntity, but maps to multiple columns in the database.

Procedure

A model of a stored procedure in the database.

Query

A model of a query. Cayenne allows queries to be mapped in Cayenne project, or created in the code. Depending on the circumstances the users may take one or the other approach.

1.3. CayenneModeler Application

Working with Mapping Projects

Reverse Engineering Database

See chapter [Reverse Engineering in Cayenne Modeler](#)

Generating Database Schema

With Cayenne Modeler you can create simple database schemas without any additional database tools. This is a good option for initial database setup if you completely created you model with the Modeler. You can start SQL schema generation by selecting menu **Tools > Generate Database Schema**

You can select what database parts should be generated and what tables you want

Migrations

Generating Java Classes

Before using Cayenne in you code you need to generate java source code for persistent objects. This can be done with Modeler GUI or via [cgen](#) maven/ant plugin.

To generate classes in the modeler use **Tools > Generate Classes**

There is three default types of code generation

- **Standard Persistent Objects**

Default type of generation suitable for almost all cases. Use this type unless you now what exactly you need to customize.

- **Client Persistent Objects**

- **Advanced**

In advanced mode you can control almost all aspects of code generation including custom templates for java code. See default Cayenne templates on GitHub as an example.

Modeling Inheritance

Modeling Generic Persistent Classes

Normally each `ObjEntity` is mapped to a specific Java class (such as `Artist` or `Painting`) that explicitly declare all entity properties as pairs of getters and setters. However Cayenne allows to map a completely generic class to any number of entities. The only expectation is that a generic class implements `org.apache.cayenne.DataObject`. So an ideal candidate for a generic class is `CayenneDataObject`, or some custom subclass of `CayenneDataObject`.

If you don't enter anything for Java Class of an `ObjEntity`, Cayenne assumes generic mapping and uses the following implicit rules to determine a class of a generic object. If `DataMap "Custom Superclass"` is set, runtime uses this class to instantiate new objects. If not, `org.apache.cayenne.CayenneDataObject` is used.

Class generation procedures (either done in the Modeler or with Ant or Maven) would skip entities that are mapped to `CayenneDataObject` explicitly or have no class mapping.

Mapping ObjAttributes to Custom Classes

Modeling Primary Key Generation Strategy

Chapter 2. Cayenne Framework

2.1. Including Cayenne in a Project

Jar Files

This is an overview of Cayenne jars that is agnostic of the build tool used. The following are the important libraries:

- `cayenne-di-4.0.RC1.jar` - Cayenne dependency injection (DI) container library. All applications will require this file.
- `cayenne-server-4.0.RC1.jar` - contains main Cayenne runtime (adapters, DB access classes, etc.). Most applications will require this file.
- `cayenne-client-4.0.RC1.jar` - a client-side runtime for [ROP applications](#)
- Other `cayenne-*` jars - various Cayenne tools extensions.

Dependencies

With modern build tools like Maven and Gradle, you should not worry about tracking dependencies. If you have one of those, you can skip this section and go straight to the Maven section below. However if your environment requires manual dependency resolution (like Ant), the distribution provides all of Cayenne jars plus a minimal set of third-party dependencies to get you started in a default configuration. Check `lib` and `lib/third-party` folders for those.

Dependencies for non-standard configurations will need to be figured out by the users on their own. Check `pom.xml` files of the corresponding Cayenne modules in one of the searchable Maven archives out there to get an idea of those dependencies (e.g. <http://search.maven.org>).

Maven Projects

If you are using Maven, you won't have to deal with figuring out the dependencies. You can simply include `cayenne-server` artifact in your POM:

```
<dependency>
  <groupId>org.apache.cayenne</groupId>
  <artifactId>cayenne-server</artifactId>
  <version>4.0.RC1</version>
</dependency>
```

Additionally Cayenne provides a Maven plugin with a set of goals to perform various project tasks, such as synching generated Java classes with the mapping, described in the following subsection. The full plugin name is `org.apache.cayenne.plugins:cayenne-maven-plugin`.

cgen

`cgen` is a `cayenne-maven-plugin` goal that generates and maintains source (.java) files of persistent

objects based on a DataMap. By default, it is bound to the generate-sources phase. If "makePairs" is set to "true" (which is the recommended default), this task will generate a pair of classes (superclass/subclass) for each ObjEntity in the DataMap. Superclasses should not be changed manually, since they are always overwritten. Subclasses are never overwritten and may be later customized by the user. If "makePairs" is set to "false", a single class will be generated for each ObjEntity.

By creating custom templates, you can use cgen to generate other output (such as web pages, reports, specialized code templates) based on DataMap information.

Table 3. cgen required parameters

Name	Type	Description
map	File	DataMap XML file which serves as a source of metadata for class generation. E.g. <div><code>\${project.basedir}/src/main/resources/my.map.xml</code></div>

Table 4. cgen optional parameters

Name	Type	Description
additionalMaps	File	A directory that contains additional DataMap XML files that may be needed to resolve cross-DataMap relationships for the the main DataMap, for which class generation occurs.
client	boolean	Whether we are generating classes for the client tier in a Remote Object Persistence application. "False" by default.
destDir	File	Root destination directory for Java classes (ignoring their package names). The default is "src/main/java".
embeddableTemplate	String	Location of a custom Velocity template file for Embeddable class generation. If omitted, default template is used.
embeddableSuperTemplate	String	Location of a custom Velocity template file for Embeddable superclass generation. Ignored unless "makepairs" set to "true". If omitted, default template is used.
encoding	String	Generated files encoding if different from the default on current platform. Target encoding must be supported by the JVM running the build. Standard encodings supported by Java on all platforms are US-ASCII, ISO-8859-1, UTF-8, UTF-16BE, UTF-16LE, UTF-16. See javadocs for <code>java.nio.charset.Charset</code> for more information.
excludeEntities	String	A comma-separated list of ObjEntity patterns (expressed as a perl5 regex) to exclude from template generation. By default none of the DataMap entities are excluded.
includeEntities	String	A comma-separated list of ObjEntity patterns (expressed as a perl5 regex) to include from template generation. By default all DataMap entities are included.

Name	Type	Description
makePairs	boolean	If "true" (a recommended default), will generate subclass/superclass pairs, with all generated code placed in superclass.
mode	String	Specifies class generator iteration target. There are three possible values: "entity" (default), "datamap", "all". "entity" performs one generator iteration for each included ObjEntity, applying either standard to custom entity templates. "datamap" performs a single iteration, applying DataMap templates. "All" is a combination of entity and datamap.
overwrite	boolean	Only has effect when "makePairs" is set to "false". If "overwrite" is "true", will overwrite older versions of generated classes.
superPkg	String	Java package name of all generated superclasses. If omitted, each superclass will be placed in the subpackage of its subclass called "auto". Doesn't have any effect if either "makepairs" or "usePkgPath" are false (both are true by default).
superTemplate	String	Location of a custom Velocity template file for ObjEntity superclass generation. Only has effect if "makepairs" set to "true". If omitted, default template is used.
template	String	Location of a custom Velocity template file for ObjEntity class generation. If omitted, default template is used.
usePkgPath	boolean	If set to "true" (default), a directory tree will be generated in "destDir" corresponding to the class package structure, if set to "false", classes will be generated in "destDir" ignoring their package.
createPropertyNames	boolean	If set to "true", will generate String Property names. Default is "false"

Example - a typical class generation scenario, where pairs of classes are generated with default Maven source destination and superclass package:

```

<plugin>
  <groupId>org.apache.cayenne.plugins</groupId>
  <artifactId>cayenne-maven-plugin</artifactId>
  <version>4.0.RC1</version>

  <configuration>
    <map>${project.basedir}/src/main/resources/my.map.xml</map>
  </configuration>

  <executions>
    <execution>
      <goals>
        <goal>cgen</goal>
      </goals>
    </execution>
  </executions>
</plugin>

```

cdbgen

cdbgen is a **cayenne-maven-plugin** goal that drops and/or generates tables in a database on Cayenne DataMap. By default, it is bound to the pre-integration-test phase.

Table 5. *cdbgen* required parameters

Name	Type	Description
map	File	DataMap XML file which serves as a source of metadata for class generation. E.g. <div> <pre> \${project.basedir}/src/main/resources/my.map.xml </pre> </div>
dataSource	XML	An object that contains Data Source parameters

Table 6. *<dataSource>* parameters

Name	Type	Required	Description
driver	String	Yes	A class of JDBC driver to use for the target database.
url	String	Yes	JDBC URL of a target database.
username	String	No	Database user name.
password	String	No	Database user password.

Table 7. *cdbgen* optional parameters

Name	Type	Description
adapter	String	Java class name implementing org.apache.cayenne.dba.DbAdapter. While this attribute is optional (a generic JdbcAdapter is used if not set), it is highly recommended to specify correct target adapter.
createFK	boolean	Indicates whether cdbgen should create foreign key constraints. Default is "true".
createPK	boolean	Indicates whether cdbgen should create Cayenne-specific auto PK objects. Default is "true".
createTables	boolean	Indicates whether cdbgen should create new tables. Default is "true".
dropPK	boolean	Indicates whether cdbgen should drop Cayenne primary key support objects. Default is "false".
dropTables	boolean	Indicates whether cdbgen should drop the tables before attempting to create new ones. Default is "false".

Example - creating a DB schema on a local HSQLDB database:

```
<plugin>
  <groupId>org.apache.cayenne.plugins</groupId>
  <artifactId>cayenne-maven-plugin</artifactId>
  <version>4.0.RC1</version>
  <executions>
    <execution>
      <configuration>
        <map>${project.basedir}/src/main/resources/my.map.xml</map>
        <adapter>org.apache.cayenne.dba.hsqldb.HSQLDBAdapter</adapter>
        <dataSource>
          <url>jdbc:hsqldb:hsql://localhost/testdb</url>
          <driver>org.hsqldb.jdbcDriver</driver>
          <username>sa</username>
        </dataSource>
      </configuration>
      <goals>
        <goal>cdbgen</goal>
      </goals>
    </execution>
  </executions>
</plugin>
```

cdimport

cdimport is a **cayenne-maven-plugin** goal that generates a DataMap based on an existing database schema. By default, it is bound to the generate-sources phase. This allows you to generate your DataMap prior to building your project, possibly followed by "cgen" execution to generate the classes. CDBImport plugin described in details in chapter [DB-First Flow](#)

Table 8. *cdbimport* parameters

Name	Type	Required	Description
map	File	Yes	DataMap XML file which is the destination of the schema import. Can be an existing file. If this file does not exist, it is created when <i>cdbimport</i> is executed. E.g. <code>\${project.basedir}/src/main/resources/my.map.xml</code> . If "overwrite" is true (the default), an existing DataMap will be used as a template for the new imported DataMap, i.e. all its entities will be cleared and recreated, but its common settings, such as default Java package, will be preserved (unless changed explicitly in the plugin configuration).
adapter	String	No	A Java class name implementing <code>org.apache.cayenne.dba.DbAdapter</code> . This attribute is optional. If not specified, <code>AutoAdapter</code> is used, which will attempt to guess the DB type.
dataSource	XML	Yes	An object that contains Data Source parameters.
dbimport	XML	No	An object that contains detailed reverse engineering rules about what DB objects should be processed. For full information about this parameter see DB-First Flow chapter.

Table 9. *<dataSource>* parameters

Name	Type	Required	Description
driver	String	Yes	A class of JDBC driver to use for the target database.
url	String	Yes	JDBC URL of a target database.
username	String	No	Database user name.
password	String	No	Database user password.

Table 10. *<dbimport>* parameters

Name	Type	Description
defaultPackage	String	A Java package that will be set as the imported DataMap default and a package of all the persistent Java classes. This is a required attribute if the "map" itself does not already contain a default package, as otherwise all the persistent classes will be mapped with no package, and will not compile.

Name	Type	Description
forceDataMapCatalog	boolean	Automatically tagging each DbEntity with the actual DB catalog/schema (default behavior) may sometimes be undesirable. If this is the case then setting <code>forceDataMapCatalog</code> to <code>true</code> will set DbEntity catalog to one in the DataMap. Default value is <code>false</code> .
forceDataMapSchema	boolean	Automatically tagging each DbEntity with the actual DB catalog/schema (default behavior) may sometimes be undesirable. If this is the case then setting <code>forceDataMapSchema</code> to <code>true</code> will set DbEntity schema to one in the DataMap. Default value is <code>false</code> .
meaningfulPkTables	String	A comma-separated list of Perl5 patterns that defines which imported tables should have their primary key columns mapped as ObjAttributes. "*" would indicate all tables.
namingStrategy	String	The naming strategy used for mapping database names to object entity names. Default is <code>org.apache.cayenne.dbsync.naming.DefaultObjectNameGenerator</code> .
skipPrimaryKeyLoading	boolean	Whether to load primary keys. Default "false".
skipRelationshipsLoading	boolean	Whether to load relationships. Default "false".
stripFromTableNames	String	<p>Regex that matches the part of the table name that needs to be stripped off when generating ObjEntity name. Here are some examples:</p> <pre> <!-- Strip prefix --> <stripFromTableNames>^myt_</stripFromTableNames> <!-- Strip suffix --> <stripFromTableNames>_s\$</stripFromTableNames> <!-- Strip multiple occurrences in the middle --> <stripFromTableNames>_abc</stripFromTableNames> </pre>
usePrimitives	boolean	Whether numeric and boolean data types should be mapped as Java primitives or Java classes. Default is "true", i.e. primitives will be used.
useJava7Types	boolean	Whether <code>DATE</code> , <code>TIME</code> and <code>TIMESTAMP</code> data types should be mapped as <code>java.util.Date</code> or <code>java.time.*</code> classes. Default is "false", i.e. <code>java.time.*</code> will be used.

Name	Type	Description
filters configuration	XML	<p>Detailed reverse engineering rules about what DB objects should be processed. For full information about this parameter see DB-First Flow chapter. Here is some simple example:</p> <pre> <dbimport> <catalog name="test_catalog"> <schema name="test_schema"> <includeTable> .*/</includeTable> <excludeTable> test_table</excludeTable> </schema> </catalog> <includeProcedure pattern=".*"/> </dbimport> </pre>

Example - loading a DB schema from a local HSQLDB database (essentially a reverse operation compared to the cdbgen example above) :

```

<plugin>
  <groupId>org.apache.cayenne.plugins</groupId>
  <artifactId>cayenne-maven-plugin</artifactId>
  <version>4.0.RC1</version>

  <executions>
    <execution>
      <configuration>
        <map>${project.basedir}/src/main/resources/my.map.xml</map>
        <dataSource>
          <url>jdbc:mysql://127.0.0.1/mydb</url>
          <driver>com.mysql.jdbc.Driver</driver>
          <username>sa</username>
        </dataSource>
        <dbimport>
          <defaultPackage>com.example.cayenne</defaultPackage>
        </dbimport>
      </configuration>
      <goals>
        <goal>cdbimport</goal>
      </goals>
    </execution>
  </executions>
</plugin>

```

Gradle Projects

To include Cayenne into your Gradle project you have two options:

- Simply add Cayenne as a dependency:

```
compile 'org.apache.cayenne:cayenne-server:4.0.RC1'
```

- Or you can use Cayenne Gradle plugin

Gradle Plugin

Cayenne Gradle plugin provides several tasks, such as synching generated Java classes with the mapping or synching mapping with the database. Plugin also provides `cayenne` extension that have some useful utility methods. Here is example of how to include Cayenne plugin into your project:

```
buildscript {
    // add Maven Central repository
    repositories {
        mavenCentral()
    }
    // add Cayenne Gradle Plugin
    dependencies {
        classpath group: 'org.apache.cayenne.plugins', name: 'cayenne-gradle-plugin',
version: '4.0.RC1'
    }
}

// apply plugin
apply plugin: 'org.apache.cayenne'

// set default DataMap
cayenne.defaultDataMap 'datamap.map.xml'

// add Cayenne dependencies to your project
dependencies {
    // this is a shortcut for 'org.apache.cayenne:cayenne-server:VERSION_OF_PLUGIN'
    compile cayenne.dependency('server')
    compile cayenne.dependency('java8')
}
```

Warning

Cayenne Gradle plugin is experimental and it's API can change later.

cgen

Cgen task generates Java classes based on your DataMap, it has same configuration parameters as in Maven Plugin version, described in [Table, “cgen required parameters”](#).. If you provided default

DataMap via `cayenne.defaultDataMap`, you can skip `cgen` configuration as default settings will suffice in common case.

Here is how you can change settings of the default `cgen` task:

```
cgen {
    client = false
    mode = 'all'
    overwrite = true
    createPropertiesNames = true
}
```

And here is example of how to define additional `cgen` task (e.g. for client classes if you are using ROP):

```
task clientCgen(type: cayenne.cgen) {
    client = true
}
```

cdbimport

This task is for creating and synchronizing your Cayenne model from database schema. Full list of parameters are same as in Maven Plugin version, described in [Table, “cdbimport parameters”](#), with exception that Gradle version will use Groovy instead of XML.

Here is example of configuration for `cdbimport` task:

```
cdbimport {
    // map can be skipped if it is defined in cayenne.defaultDataMap
    map 'datamap.map.xml'

    dataSource {
        driver 'com.mysql.cj.jdbc.Driver'
        url 'jdbc:mysql://127.0.0.1:3306/test?useSSL=false'
        username 'root'
        password ''
    }

    dbImport
        // additional settings
        usePrimitives false
        defaultPackage 'org.apache.cayenne.test'

        // DB filter configuration
        catalog 'catalog-1'
        schema 'schema-1'

        catalog {
```

```

    name 'catalog-2'

    includeTable 'table0', {
        excludeColumns '_column_'
    }

    includeTables 'table1', 'table2', 'table3'

    includeTable 'table4', {
        includeColumns 'id', 'type', 'data'
    }

    excludeTable '^GENERATED_.*'
}

catalog {
    name 'catalog-3'
    schema {
        name 'schema-2'
        includeTable 'test_table'
        includeTable 'test_table2', {
            excludeColumn '__excluded'
        }
    }
}

includeProcedure 'procedure_test_1'

includeColumns 'id', 'version'

tableTypes 'TABLE', 'VIEW'
}

```

cdbgen

Cdbgen task drops and/or generates tables in a database on Cayenne DataMap. Full list of parameters are same as in Maven Plugin version, described in [Table](#) , “[cdbgen required parameters](#)”

Here is example of how to configure default **cdbgen** task:

```

cdbgen {

    adapter 'org.apache.cayenne.dba.derby.DerbyAdapter'

    dataSource {
        driver 'org.apache.derby.jdbc.EmbeddedDriver'
        url 'jdbc:derby:build/testdb;create=true'
        username 'sa'
        password ''
    }

    dropTables true
    dropPk true

    createTables true
    createPk true
    createFk true
}

```

Link tasks to Gradle build lifecycle

With gradle you can easily connect Cayenne tasks to default build lifecycle. Here is short example of how to connect default `cgen` and `cdbimport` tasks with `compileJava` task:

```

cgen.dependsOn cdbimport
compileJava.dependsOn cgen

```



Running `cdbimport` automatically with build not always a good choice, e.g. in case of complex model that you need to alter in the Cayenne Modeler after import.

Ant Projects

Ant tasks are the same as Maven plugin goals described above, namely "cgen", "cdbgen", "cdbimport". Configuration parameters are also similar (except Maven can guess many defaults that Ant can't). To include Ant tasks in the project, use the following Antlib:

```

<typedef resource="org/apache/cayenne/tools/antlib.xml">
  <classpath>
    <fileset dir="lib" >
      <include name="cayenne-ant-*.jar" />
      <include name="cayenne-cgen-*.jar" />
      <include name="cayenne-dbsync-*.jar" />
      <include name="cayenne-di-*.jar" />
      <include name="cayenne-project-*.jar" />
      <include name="cayenne-server-*.jar" />
      <include name="commons-collections-*.jar" />
      <include name="commons-lang-*.jar" />
      <include name="slf4j-api-*.jar" />
      <include name="velocity-*.jar" />
      <include name="vpp-2.2.1.jar" />
    </fileset>
  </classpath>
</typedef>

```

cgen

cdbgen

cdbimport

This is an Ant counterpart of "cdbimport" goal of cayenne-maven-plugin described above. It has exactly the same properties. Here is a usage example:

```

<cdbimport map="${context.dir}/WEB-INF/my.map.xml"
  driver="com.mysql.jdbc.Driver"
  url="jdbc:mysql://127.0.0.1/mydb"
  username="sa"
  defaultPackage="com.example.cayenne"/>

```

2.2. Starting Cayenne

Starting and Stopping ServerRuntime

In runtime Cayenne is accessed via `org.apache.cayenne.configuration.server.ServerRuntime`. `ServerRuntime` is created by calling a convenient builder:

```

ServerRuntime runtime = ServerRuntime.builder()
    .addConfig("com/example/cayenne-project.xml")
    .build();

```

The parameter you pass to the builder is a location of the main project file. Location is a '/'-separated path (same path separator is used on UNIX and Windows) that is resolved relative to the

application classpath. The project file can be placed in the root package or in a subpackage (e.g. in the code above it is in "com/example" subpackage).

ServerRuntime encapsulates a single Cayenne stack. Most applications will just have one ServerRuntime using it to create as many ObjectContexts as needed, access the Dependency Injection (DI) container and work with other Cayenne features. Internally ServerRuntime is just a thin wrapper around the DI container. Detailed features of the container are discussed in [Customizing Cayenne Runtime](#) chapter. Here we'll just show an example of how an application might turn on external transactions:

```
Module extensions = binder ->
    ServerModule.contributeProperties(binder).put(Constants
.SERVER_EXTERNAL_TX_PROPERTY, "true");
ServerRuntime runtime = ServerRuntime.builder()
    .addConfig("com/example/cayenne-project.xml")
    .addModule(extensions)
    .build();
```

It is a good idea to shut down the runtime when it is no longer needed, usually before the application itself is shutdown:

```
runtime.shutdown();
```

When a runtime object has the same scope as the application, this may not be always necessary, however in some cases it is essential, and is generally considered a good practice. E.g. in a web container hot redeploy of a webapp will cause resource leaks and eventual OutOfMemoryError if the application fails to shutdown CayenneRuntime.

Merging Multiple Projects

ServerRuntime requires at least one mapping project to run. But it can also take multiple projects and merge them together in a single configuration. This way different parts of a database can be mapped independently from each other (even by different software providers), and combined in runtime when assembling an application. Doing it is as easy as passing multiple project locations to ServerRuntime builder:

```
ServerRuntime runtime = ServerRuntime.builder()
    .addConfig("com/example/cayenne-project.xml")
    .addConfig("org/foo/cayenne-library1.xml")
    .addConfig("org/foo/cayenne-library2.xml")
    .build();
```

When the projects are merged, the following rules are applied:

- The order of projects matters during merge. If there are two conflicting metadata objects belonging to two projects, an object from the last project takes precedence over the object from

the first one. This makes possible to override pieces of metadata. This is also similar to how DI modules are merged in Cayenne.

- Runtime `DataDomain` name is set to the name of the last project in the list.
- Runtime `DataDomain` properties are the same as the properties of the last project in the list. I.e. properties are not merged to avoid invalid combinations and unexpected runtime behavior.
- If there are two or more `DataMaps` with the same name, only one `DataMap` is used in the merged project, the rest are discarded. Same precedence rules apply - `DataMap` from the project with the highest index in the project list overrides all other `DataMaps` with the same name.
- If there are two or more `DataNodes` with the same name, only one `DataNodes` is used in the merged project, the rest are discarded. `DataNode` coming from project with the highest index in the project list is chosen per precedence rule above.
- There is a notion of "default" `DataNode`. After the merge if any `DataMaps` are not explicitly linked to `DataNodes`, their queries will be executed via a default `DataNode`. This makes it possible to build mapping "libraries" that are only associated with a specific database in runtime. If there's only one `DataNode` in the merged project, it will be automatically chosen as default. A possible way to explicitly designate a specific node as default is to override `DataDomainProvider.createAndInitDataDomain()`.

Web Applications

Web applications can use a variety of mechanisms to configure and start the "services" they need, Cayenne being one of such services. Configuration can be done within standard Servlet specification objects like Servlets, Filters, or `ServletContextListeners`, or can use Spring, JEE CDI, etc. This is a user's architectural choice and Cayenne is agnostic to it and will happily work in any environment. As described above, all that is needed is to create an instance of `ServerRuntime` somewhere and provide the application code with means to access it. And shut it down when the application ends to avoid container leaks.

Still Cayenne includes a piece of web app configuration code that can assist in quickly setting up simple Cayenne-enabled web applications. We are talking about `CayenneFilter`. It is declared in `web.xml`:

```
<web-app>
...
  <filter>
    <filter-name>cayenne-project</filter-name>
    <filter-class>org.apache.cayenne.configuration.web.CayenneFilter</filter-
class>
  </filter>
  <filter-mapping>
    <filter-name>cayenne-project</filter-name>
    <url-pattern>/*</url-pattern>
  </filter-mapping>
...
</web-app>
```

When started by the web container, it creates a instance of `ServerRuntime` and stores it in the `ServletContext`. Note that the name of Cayenne XML project file is derived from the "filter-name". In the example above `CayenneFilter` will look for an XML file "cayenne-project.xml". This can be overridden with "configuration-location" init parameter.

When the application runs, all HTTP requests matching the filter url-pattern will have access to a session-scoped `ObjectContext` like this:

```
ObjectContext context = BaseContext.getThreadObjectContext();
```

Of course the `ObjectContext` scope, and other behavior of the Cayenne runtime can be customized via dependency injection. For this another filter init parameter called "extra-modules" is used. "extra-modules" is a comma or space-separated list of class names, with each class implementing `Module` interface. These optional custom modules are loaded after the the standard ones, which allows users to override all standard definitions.

For those interested in the DI container contents of the runtime created by `CayenneFilter`, it is the same `ServerRuntime` as would've been created by other means, but with an extra `org.apache.cayenne.configuration.web.WebModule` module that provides `org.apache.cayenne.configuration.web.RequestHandler` service. This is the service to override in the custom modules if you need to provide a different `ObjectContext` scope, etc.



You should not think of `CayenneFilter` as the only way to start and use Cayenne in a web application. In fact `CayenneFilter` is entirely optional. Use it if you don't have any special design for application service management. If you do, simply integrate Cayenne into that design.

2.3. Persistent Objects and ObjectContext

ObjectContext

`ObjectContext` is an interface that users normally work with to access the database. It provides the API to execute database operations and to manage persistent objects. A context is obtained from the `ServerRuntime`:

```
ObjectContext context = runtime.newContext();
```

The call above creates a new instance of `ObjectContext` that can access the database via this runtime. `ObjectContext` is a single "work area" in Cayenne, storing persistent objects. `ObjectContext` guarantees that for each database row with a unique ID it will contain at most one instance of an object, thus ensuring object graph consistency between multiple selects (a feature called "uniquing"). At the same time different `ObjectContexts` will have independent copies of objects for each unique database row. This allows users to isolate object changes from one another by using separate `ObjectContexts`.

These properties directly affect the strategies for scoping and sharing (or not sharing)

ObjectContexts. Contexts that are only used to fetch objects from the database and whose objects are never modified by the application can be shared between multiple users (and multiple threads). Contexts that store modified objects should be accessed only by a single user (e.g. a web application user might reuse a context instance between multiple web requests in the same HttpSession, thus carrying uncommitted changes to objects from request to request, until he decides to commit or rollback them). Even for a single user it might make sense to use multiple ObjectContexts (e.g. request-scoped contexts to allow concurrent requests from the browser that change and commit objects independently).

ObjectContext is serializable and does not permanently hold to any of the application resources. So it does not have to be closed. If the context is not used anymore, it should simply be allowed to go out of scope and get garbage collected, just like any other Java object.

Persistent Object and its Lifecycle

Cayenne can persist Java objects that implement `org.apache.cayenne.Persistent` interface. Generally persistent classes are generated from the model as described above, so users do not have to worry about superclass and property implementation details.

Persistent interface provides access to 3 persistence-related properties - `objectId`, `persistenceState` and `objectContext`. All 3 are initialized by Cayenne runtime framework. Application code should not attempt to change them. However it is allowed to read them, which provides valuable runtime information. E.g. `ObjectId` can be used for quick equality check of 2 objects, knowing persistence state would allow highlighting changed objects, etc.

Each persistent object belongs to a single ObjectContext, and can be in one of the following persistence states (as defined in `org.apache.cayenne.PersistenceState`) :

Table 11. Persistence States

TRANSIENT	The object is not registered with an ObjectContext and will not be persisted.
NEW	The object is freshly registered in an ObjectContext, but has not been saved to the database yet and there is no matching database row.
COMMITTED	The object is registered in an ObjectContext, there is a row in the database corresponding to this object, and the object state corresponds to the last known state of the matching database row.
MODIFIED	The object is registered in an ObjectContext, there is a row in the database corresponding to this object, but the object in-memory state has diverged from the last known state of the matching database row.
HOLLOW	The object is registered in an ObjectContext, there is a row in the database corresponding to this object, but the object state is unknown. Whenever an application tries to access a property of such object, Cayenne attempts reading its values from the database and "inflate" the object, turning it to COMMITTED.
DELETED	The object is registered in an ObjectContext and has been marked for deletion in-memory. The corresponding row in the database will get deleted upon ObjectContext commit, and the object state will be turned into TRANSIENT.

ObjectContext Persistence API

One of the first things users usually want to do with an `ObjectContext` is to select some objects from a database:

```
List<Artist> artists = ObjectSelect.query(Artist.class)
    .select(context);
```

We'll discuss queries in some detail in the [Queries](#) chapter. The example above is self-explanatory - we create a `ObjectSelect` that matches all `Artist` objects present in the database, and then use `select` to get the result.

Some queries can be quite complex, returning multiple result sets or even updating the database. For such queries `ObjectContext` provides `performGenericQuery()` method. While not commonly-used, it is nevertheless important in some situations. E.g.:

```
Collection<Query> queries = ... // multiple queries that need to be run together
QueryChain query = new QueryChain(queries);

QueryResponse response = context.performGenericQuery(query);
```

An application might modify selected objects. E.g.:

```
Artist selectedArtist = artists.get(0);
selectedArtist.setName("Dali");
```

The first time the object property is changed, the object's state is automatically set to **MODIFIED** by Cayenne. Cayenne tracks all in-memory changes until a user calls `commitChanges`:

```
context.commitChanges();
```

At this point all in-memory changes are analyzed and a minimal set of SQL statements is issued in a single transaction to synchronize the database with the in-memory state. In our example `commitChanges` commits just one object, but generally it can be any number of objects.

If instead of commit, we wanted to reset all changed objects to the previously committed state, we'd call `rollbackChanges` instead:

```
context.rollbackChanges();
```

`newObject` method call creates a persistent object and sets its state to **NEW**:

```
Artist newArtist = context.newObject(Artist.class);
newArtist.setName("Picasso");
```

It will only exist in memory until `commitChanges` is issued. On commit Cayenne might generate a new primary key (unless a user set it explicitly, or a PK was inferred from a relationship) and issue an `INSERT` SQL statement to permanently store the object.

`deleteObjects` method takes one or more Persistent objects and marks them as **DELETED**:

```
context.deleteObjects(artist1);
context.deleteObjects(artist2, artist3, artist4);
```

Additionally `deleteObjects` processes all delete rules modeled for the affected objects. This may result in implicitly deleting or modifying extra related objects. Same as insert and update, delete operations are sent to the database only when `commitChanges` is called. Similarly `rollbackChanges` will undo the effect of `newObject` and `deleteObjects`.

`localObject` returns a copy of a given persistent object that is *local* to a given `ObjectContext`:

Since an application often works with more than one context, `localObject` is a rather common operation. E.g. to improve performance a user might utilize a single shared context to select and cache data, and then occasionally transfer some selected objects to another context to modify and commit them:

```
ObjectContext editingContext = runtime.newContext();
Artist localArtist = editingContext.localObject(artist);
```

Often an application needs to inspect mapping metadata. This information is stored in the `EntityResolver` object, accessible via the `ObjectContext`:

```
EntityResolver resolver = objectContext.getEntityResolver();
```

Here we discussed the most commonly used subset of the `ObjectContext` API. There are other useful methods, e.g. those allowing to inspect registered objects state in bulk, etc. Check the latest JavaDocs for details.

Cayenne Helper Class

There is a useful helper class called `Cayenne` (fully-qualified name `org.apache.cayenne.Cayenne`) that builds on `ObjectContext` API to provide a number of very common operations. E.g. get a primary key (most entities do not model PK as an object property) :

```
long pk = Cayenne.longPKForObject(artist);
```

It also provides the reverse operation - finding an object given a known PK:

```
Artist artist = Cayenne.objectForPK(context, Artist.class, 34579);
```

If a query is expected to return 0 or 1 object, Cayenne helper class can be used to find this object. It throws an exception if more than one object matched the query:

```
Artist artist = (Artist) Cayenne.objectForQuery(context, new SelectQuery(Artist.class));
```

Feel free to explore Cayenne class API for other useful methods.

ObjectContext Nesting

In all the examples shown so far an ObjectContext would directly connect to a database to select data or synchronize its state (either via commit or rollback). However another context can be used in all these scenarios instead of a database. This concept is called ObjectContext "nesting". Nesting is a parent/child relationship between two contexts, where child is a nested context and selects or commits its objects via a parent.

Nesting is useful to create isolated object editing areas (child contexts) that need to all be committed to an intermediate in-memory store (parent context), or rolled back without affecting changes already recorded in the parent. Think cascading GUI dialogs, or parallel AJAX requests coming to the same session.

In theory Cayenne supports any number of nesting levels, however applications should generally stay with one or two, as deep hierarchies will most certainly degrade the performance of the deeply nested child contexts. This is due to the fact that each context in a nesting chain has to update its own objects during most operations.

Cayenne ROP is an extreme case of nesting when a child context is located in a separate JVM and communicates with its parent via a web service. ROP is discussed in details in the following chapters. Here we concentrate on the same-VM nesting.

To create a nested context, use an instance of `ServerRuntime`, passing it the desired parent:

```
ObjectContext parent = runtime.newContext();  
ObjectContext nested = runtime.newContext(parent);
```

From here a nested context operates just like a regular context (you can perform queries, create and delete objects, etc.). The only difference is that commit and rollback operations can either be limited to synchronization with the parent, or cascade all the way to the database:

```
// merges nested context changes into the parent context
nested.commitChangesToParent();

// regular 'commitChanges' cascades commit through the chain
// of parent contexts all the way to the database
nested.commitChanges();
```

```
// unrolls all local changes, getting context in a state identical to parent
nested.rollbackChangesLocally();

// regular 'rollbackChanges' cascades rollback through the chain of contexts
// all the way to the topmost parent
nested.rollbackChanges();
```

Generic Persistent Objects

As described in the CayenneModeler chapter, Cayenne supports mapping of completely generic classes to specific entities. Although for convenience most applications should stick with entity-specific class mappings, the generic feature offers some interesting possibilities, such as creating mappings completely on the fly in a running application, etc.

Generic objects are first class citizens in Cayenne, and all common persistent operations apply to them as well. There are some peculiarities however, described below.

When creating a new generic object, either cast your `ObjectContext` to `DataContext` (that provides `newObject(String)` API), or provide your object with an explicit `ObjectId`:

```
DataObject generic = ((DataContext) context).newObject("GenericEntity");
```

```
DataObject generic = new CayenneDataObject();
generic.setObjectId(new ObjectId("GenericEntity"));
context.registerNewObject(generic);
```

`SelectQuery` for generic object should be created passing entity name `String` in constructor, instead of a Java class:

```
SelectQuery query = new SelectQuery("GenericEntity");
```

Use `DataObject` API to access and modify properties of a generic object:

```
String name = (String) generic.readProperty("name");
generic.writeProperty("name", "New Name");
```

This is how an application can obtain entity name of a generic object:

```
String entityName = generic.getObjectId().getEntityName();
```

Transactions

Considering how much attention is given to managing transactions in most other ORMs, transactions have been conspicuously absent from the ObjectContext discussion till now. The reason is that transactions are seamless in Cayenne in all but a few special cases. ObjectContext is an in-memory container of objects that is disconnected from the database, except when it needs to run an operation. So it does not care about any surrounding transaction scope. Sure enough all database operations are transactional, so when an application does a commit, all SQL execution is wrapped in a database transaction. But this is done behind the scenes and is rarely a concern to the application code.

Two cases where transactions need to be taken into consideration are container-managed and application-managed transactions.

If you are using an EJB container (or some other JTA environment), you'll likely need to switch Cayenne runtime into "external transactions mode". This is done by setting DI configuration property defined in `Constants.SERVER_EXTERNAL_TX_PROPERTY` (see Appendix A). If this property is set to "true", Cayenne assumes that JDBC Connections obtained by runtime whenever that might happen are all coming from a transactional DataSource managed by the container. In this case Cayenne does not attempt to commit or rollback the connections, leaving it up to the container to do that when appropriate.

In the second scenario, an application might need to define its own transaction scope that spans more than one Cayenne operation. E.g. two sequential commits that need to be rolled back together in case of failure. This can be done via `ServerRuntime.performInTransaction` method:

```
Integer result = runtime.performInTransaction(() -> {
    // commit one or more contexts
    context1.commitChanges();
    context2.commitChanges();
    ....
    // after changing some objects in context1, commit again
    context1.commitChanges();
    ....

    // return an arbitrary result or null if we don't care about the result
    return 5;
});
```

When inside the transaction, current thread Transaction object can be accessed via a static method. E.g. here is an example that initializes transaction JDBC connection with a custom connection object :

```
Transaction tx = BaseTransaction.getThreadTransaction();
tx.addConnection("mydatanode", myConnection);
```

2.4. Expressions

Expressions Overview

Cayenne provides a simple yet powerful object-based expression language. The most common use of expressions are to build qualifiers and orderings of queries that are later converted to SQL by Cayenne and to evaluate in-memory against specific objects (to access certain values in the object graph or to perform in-memory object filtering and sorting). Cayenne provides API to build expressions in the code and a parser to create expressions from strings.

Path Expressions

Before discussing how to build expressions, it is important to understand one group of expressions widely used in Cayenne - path expressions. There are two types of path expressions - object and database, used for navigating graphs of connected objects or joined DB tables respectively. Object paths are much more commonly used, as after all Cayenne is supposed to provide a degree of isolation of the object model from the database. However database paths are helpful in certain situations. General structure of path expressions is the following:

```
[db:]segment[+][.segment[+]...]
```

- **db:** is an optional prefix indicating that the following path is a DB path. Otherwise it is an object path.
- **segment** is a name of a property (relationship or attribute in Cayenne terms) in the path. Path must have at least one segment; segments are separated by dot (".").
- **+** An "OUTER JOIN" path component. Currently "+" only has effect when translated to SQL as OUTER JOIN. When evaluating expressions in memory, it is ignored.

An object path expression represents a chain of property names rooted in a certain (unspecified during expression creation) object and "navigating" to its related value. E.g. a path expression "artist.name" might be a property path starting from a Painting object, pointing to the related Artist object, and then to its name attribute. A few more examples:

- **name** - can be used to navigate (read) the "name" property of a Person (or any other type of object that has a "name" property).
- **artist.exhibits.closingDate** - can be used to navigate to a closing date of any of the exhibits of a Painting's Artist object.
- **artist.exhibits+.closingDate** - same as the previous example, but when translated into SQL, an OUTER JOIN will be used for "exhibits".

Similarly a database path expression is a dot-separated path through DB table joins and columns. In

Cayenne joins are mapped as DbRelationships with some symbolic names (the closest concept to DbRelationship name in the DB world is a named foreign key constraint. But DbRelationship names are usually chosen arbitrarily, without regard to constraints naming or even constraints presence). A database path therefore might look like this - `db:dbrelationshipX.dbrelationshipY.COLUMN_Z`. More specific examples:

- `db:NAME` - can be used to navigate to the value of "NAME" column of some unspecified table.
- `db:artist.artistExhibits.exhibit.CLOSING_DATE` - can be used to match a closing date of any of the exhibits of a related artist record.

Cayenne supports "aliases" in path Expressions. E.g. the same expression can be written using explicit path or an alias:

- `artist.exhibits.closingDate` - full path
- `e.closingDate` - alias `e` is used for `artist.exhibits`.

SelectQuery using the second form of the path expression must be made aware of the alias via `SelectQuery.aliasPathSplits(..)`, otherwise an Exception will be thrown. The main use of aliases is to allow users to control how SQL joins are generated if the same path is encountered more than once in any given Expression. Each alias for any given path would result in a separate join. Without aliases, a single join will be used for a group of matching paths.

Creating Expressions from Strings

While in most cases users are likely to rely on API from the following section for expression creation, we'll start by showing String expressions, as this will help to understand the semantics. A Cayenne expression can be represented as a String, which can be converted to an expression object using `ExpressionFactory.exp` static method. Here is an example:

```
String expString = "name like 'A%' and price < 1000";
Expression exp = ExpressionFactory.exp(expString);
```

This particular expression may be used to match Paintings whose names that start with "A" and whose price is less than \$1000. While this example is pretty self-explanatory, there are a few points worth mentioning. "name" and "price" here are object paths discussed earlier. As always, paths themselves are not attached to a specific root entity and can be applied to any entity that has similarly named attributes or relationships. So when we are saying that this expression "may be used to match Paintings", we are implying that there may be other entities, for which this expression is valid. Now the expression details...

Character constants that are not paths or numeric values should be enclosed in single or double quotes. Two of the expressions below are equivalent:

```
name = 'ABC'

// double quotes are escaped inside Java Strings of course
name = "\"ABC\""
```

Case sensitivity. Expression operators are case sensitive and are usually lowercase. Complex words follow the Java camel-case style:

```
// valid
name likeIgnoreCase 'A%'

// invalid - will throw a parse exception
name LIKEIGNORECASE 'A%'
```

Grouping with parenthesis:

```
value = (price + 250.00) * 3
```

Path prefixes. Object expressions are unquoted strings, optionally prefixed by "obj:" (usually they are not prefixed at all actually). Database expressions are always prefixed with "db:". A special kind of prefix, not discussed yet is "enum:" that prefixes an enumeration constant:

```
// object path
name = 'Salvador Dali'

// same object path - a rarely used form
obj:name = 'Salvador Dali'

// multi-segment object path
artist.name = 'Salvador Dali'

// db path
db:NAME = 'Salvador Dali'

// enumeration constant
name = enum:org.foo.EnumClass.VALUE1
```

Binary conditions are expressions that contain a path on the left, a value on the right, and some operation between them, such as equals, like, etc. They can be used as qualifiers in SelectQueries:

```
name like 'A%'
```

Parameters. Expressions can contain named parameters (names that start with "\$") that can be substituted with values either by name or by position. Parameterized expressions allow to create

reusable expression templates. Also if an Expression contains a complex object that doesn't have a simple String representation (e.g. a Date, a DataObject, an ObjectId), parameterizing such expression is the only way to represent it as String. Here are the examples of both positional and named parameter bindings:

```
Expression template = ExpressionFactory.exp("name = $name");
...
// name binding
Map p1 = Collections.singletonMap("name", "Salvador Dali");
Expression qualifier1 = template.params(p1);
...
// positional binding
Expression qualifier2 = template.paramsArray("Monet");
```

Positional binding is usually shorter. You can pass positional bindings to the `exp(..)` factory method (its second argument is a params vararg):

```
Expression qualifier = ExpressionFactory.exp("name = $name", "Monet");
```

In parameterized expressions with LIKE clause, SQL wildcards must be part of the values in the Map and not the expression string itself:

```
Expression qualifier = ExpressionFactory.exp("name like $name", "Salvador%");
```

When matching on a relationship, the value parameter must be either a Persistent object, an `org.apache.cayenne.ObjectId`, or a numeric ID value (for single column IDs). E.g.:

```
Artist dali = ... // assume we fetched this one already
Expression qualifier = ExpressionFactory.exp("artist = $artist", dali);
```

When using positional binding, Cayenne would expect values for all parameters to be present. Binding by name offers extra flexibility: subexpressions with uninitialized parameters are automatically pruned from the expression. So e.g. if certain parts of the expression criteria are not provided to the application, you can still build a valid expression:

```
Expression template = ExpressionFactory.exp("name like $name and dateOfBirth > $date"
);
...
Map p1 = Collections.singletonMap("name", "Salvador%");
Expression qualifier1 = template.params(p1);

// "qualifier1" is now "name like 'Salvador%'".
// 'dateOfBirth > $date' condition was pruned, as no value was specified for
// the $date parameter
```

Null handling. Handling of Java nulls as operands is no different from normal values. Instead of using special conditional operators, like SQL does (IS NULL, IS NOT NULL), "=" and "!=" expressions are used directly with null values. It is up to Cayenne to translate expressions with nulls to the valid SQL.



A formal definition of the expression grammar is provided in [Appendix C](#)

Creating Expressions via API

Creating expressions from Strings is a powerful and dynamic approach, however a safer alternative is to use Java API. It provides compile-time checking of expressions validity. The API in question is provided by `ExpressionFactory` class (that we've seen already), `Property` class and `Expression` class itself. `ExpressionFactory` contains a number of self-explanatory static methods that can be used to build expressions. E.g.:

```
// String expression: name like 'A%' and price < 1000
Expression e1 = ExpressionFactory.likeExp("name", "A%");
Expression e2 = ExpressionFactory.lessExp("price", 1000);
Expression finalExp = e1.andExp(e2);
```



The last line in the example above shows how to create a new expression by "chaining" two other expressions. A common error when chaining expressions is to assume that "andExp" and "orExp" append another expression to the current expression. In fact a new expression is created. I.e. Expression API treats existing expressions as immutable.

As discussed earlier, Cayenne supports aliases in path Expressions, allowing to control how SQL joins are generated if the same path is encountered more than once in the same Expression. Two `ExpressionFactory` methods allow to implicitly generate aliases to "split" match paths into individual joins if needed:

```
Expression matchAllExp(String path, Collection values)
Expression matchAllExp(String path, Object... values)
```

"Path" argument to both of these methods can use a split character (a pipe symbol '|') instead of dot to indicate that relationship following a path should be split into a separate set of joins, one per collection value. There can only be one split at most in any given path. Split must always precede a relationship. E.g. "`|exhibits.paintings`", "`exhibits|paintings`", etc. Internally Cayenne would generate distinct aliases for each of the split expressions, forcing separate joins.

While `ExpressionFactory` is pretty powerful, there's an even easier way to create expression using static `Property` objects generated by Cayenne for each persistent class. Some examples:

```
// Artist.NAME is generated by Cayenne and has a type of Property<String>
Expression e1 = Artist.NAME.eq("Pablo");

// Chaining multiple properties into a path..
// Painting.ARTIST is generated by Cayenne and has a type of Property<Artist>
Expression e2 = Painting.ARTIST.dot(Artist.NAME).eq("Pablo");
```

Property objects provide the API mostly analogous to ExpressionFactory, though it is significantly shorter and is aware of the value types. It provides compile-time checks of both property names and types of arguments in conditions. We will use Property-based API in further examples.

Evaluating Expressions in Memory

When used in a query, an expression is converted to SQL WHERE clause (or ORDER BY clause) by Cayenne during query execution. Thus the actual evaluation against the data is done by the database engine. However the same expressions can also be used for accessing object properties, calculating values, in-memory filtering.

Checking whether an object satisfies an expression:

```
Expression e = Artist.NAME.in("John", "Bob");
Artist artist = ...
if(e.match(artist)) {
    ...
}
```

Reading property value:

```
String name = Artist.NAME.path().evaluate(artist);
```

Filtering a list of objects:

```
Expression e = Artist.NAME.in("John", "Bob");
List<Artist> unfiltered = ...
List<Artist> filtered = e.filterObjects(unfiltered);
```



Current limitation of in-memory expressions is that no collections are permitted in the property path.

Translating Expressions to EJBQL

EJBQL is a textual query language that can be used with Cayenne. In some situations, it is convenient to be able to convert Expression instances into EJBQL. Expressions support this conversion. An example is shown below.

```
String serial = ...
Expression e = Pkg.SERIAL.eq(serial);
List<Object> params = new ArrayList<Object>();
EJBQLQuery query = new EJBQLQuery("SELECT p FROM Pkg p WHERE " + e.toEJBQL(params,"p"
));

for(int i=0;i<params.size();i++) {
    query.setParameter(i+1, params.get(i));
}
```

This would be equivalent to the following purely EJBQL querying logic;

```
EJBQLQuery query = new EJBQLQuery("SELECT p FROM Pkg p WHERE p.serial = ?1");
query.setParameter(1,serial);
```

2.5. Orderings

An Ordering object defines how a list of objects should be ordered. Orderings are essentially path expressions combined with a sorting strategy. Creating an Ordering:

```
Ordering o = new Ordering(Painting.NAME_PROPERTY, SortOrder.ASCENDING);
```

Like expressions, orderings are translated into SQL as parts of queries (and the sorting occurs in the database). Also like expressions, orderings can be used in memory, naturally - to sort objects:

```
Ordering o = new Ordering(Painting.NAME_PROPERTY, SortOrder.ASCENDING_INSENSITIVE);
List<Painting> list = ...
o.orderList(list);
```

Note that unlike filtering with Expressions, ordering is performed in-place. This list object is reordered and no new list is created.

2.6. Queries

Queries are Java objects used by the application to communicate with the database. Cayenne knows how to translate queries into SQL statements appropriate for a particular database engine. Most often queries are used to find objects matching certain criteria, but there are other types of queries too. E.g. those allowing to run native SQL, call DB stored procedures, etc. When committing objects, Cayenne itself creates special queries to insert/update/delete rows in the database.

There is a number of built-in queries in Cayenne, described later in this chapter. Most of the newer queries use fluent API and can be created and executed as easy-to-read one-liners. Users can define their own query types to abstract certain DB interactions that for whatever reason can not be adequately described by the built-in set.

Queries can be roughly categorized as "object" and "native". Object queries (most notably `ObjectSelect`, `SelectById`, and `EJBQLQuery`) are built with abstractions originating in the object model (the "object" side in the "object-relational" divide). E.g. `ObjectSelect` is assembled from a Java class of the objects to fetch, a qualifier expression, orderings, etc. - all of this expressed in terms of the object model.

Native queries describe a desired DB operation as SQL code (`SQLSelect`, `SQLTemplate` query) or a reference to a stored procedure (`ProcedureQuery`), etc. The results of native queries are usually presented as Lists of Maps, with each map representing a row in the DB (a term "data row" is often used to describe such a map). They can potentially be converted to objects, however it may take a considerable effort to do so. Native queries are also less (if at all) portable across databases than object queries.

ObjectSelect

Selecting objects

`ObjectSelect` supersedes older `SelectQuery`. `SelectQuery` is still available and supported.

`ObjectSelect` is the most commonly used query in Cayenne applications. This may be the only query you will ever need. It returns a list of persistent objects (or data rows) of a certain type specified in the query:

```
List<Artist> objects = ObjectSelect.query(Artist.class).select(context);
```

This returned all rows in the "ARTIST" table. If the logs were turned on, you might see the following SQL printed:

```
INFO: SELECT t0.DATE_OF_BIRTH, t0.NAME, t0.ID FROM ARTIST t0
INFO: === returned 5 row. - took 5 ms.
```

This SQL was generated by Cayenne from the `ObjectSelect` above. `ObjectSelect` can have a qualifier to select only the data matching specific criteria. Qualifier is simply an `Expression` (Expressions where discussed in the previous chapter), appended to the query using "where" method. If you only want artists whose name begins with 'Pablo', you might use the following qualifier expression:

```
List<Artist> objects = ObjectSelect.query(Artist.class)
    .where(Artist.NAME.like("Pablo%"))
    .select(context);
```

The SQL will look different this time:

```
INFO: SELECT t0.DATE_OF_BIRTH, t0.NAME, t0.ID FROM ARTIST t0 WHERE t0.NAME LIKE ?
[bind: 1->NAME:'Pablo%']
INFO: === returned 1 row. - took 6 ms.
```

ObjectSelect allows to assemble qualifier from parts, using "and" and "or" method to chain them together:

```
List<Artist> objects = ObjectSelect.query(Artist.class)
    .where(Artist.NAME.like("A%"))
    .and(Artist.DATE_OF_BIRTH.gt(someDate))
    .select(context);
```

To order the results of ObjectSelect, one or more orderings can be applied:

```
List<Artist> objects = ObjectSelect.query(Artist.class)
    .orderBy(Artist.DATE_OF_BIRTH.desc())
    .orderBy(Artist.NAME.asc())
    .select(context);
```

There's a number of other useful methods in ObjectSelect that define what to select and how to optimize database interaction (prefetching, caching, fetch offset and limit, pagination, etc.). Some of them are discussed in separate chapters on caching and performance optimization. Others are fairly self-explanatory. Please check the API docs for the full extent of the ObjectSelect features.

Selecting individual columns

ObjectSelect query can be used to fetch individual properties of objects via type-safe API:

```
List<String> names = ObjectSelect.columnQuery(Artist.class, Artist.ARTIST_NAME)
    .select(context);
```

And here is example of selecting several properties, note that result will be **Object[]**:

```
List<Object[]> nameAndDate = ObjectSelect
    .columnQuery(Artist.class, Artist.ARTIST_NAME, Artist.DATE_OF_BIRTH)
    .select(context);
```

Selecting using aggregate functions

ObjectSelect query supports usage of aggregate functions. Most common variant of aggregation is selecting count of records, this can be done really easy:

```
long count = ObjectSelect.query(Artist.class).selectCount(context);
```

But you can use aggregates in more cases, even combine selecting individual properties and aggregates:

```
// this is artificial property signaling that we want to get full object
Property<Artist> artistProperty = Property.createSelf(Artist.class);

List<Object[]> artistAndPaintingCount = ObjectSelect.columnQuery(Artist.class,
artistProperty, Artist.PAINTING_ARRAY.count())
    .where(Artist.ARTIST_NAME.like("a%"))
    .having(Artist.PAINTING_ARRAY.count().lt(5L))
    .orderBy(Artist.PAINTING_ARRAY.count().desc(), Artist.ARTIST_NAME.asc())
    .select(context);

for(Object[] next : artistAndPaintingCount) {
    Artist artist = (Artist)next[0];
    long paintings = (Long)next[1];
    System.out.println(artist.getArtistName() + " have " + paintings + " paintings");
}
```

Here is generated SQL for this query:

```
SELECT DISTINCT t0.ARTIST_NAME, t0.DATE_OF_BIRTH, t0.ARTIST_ID, COUNT(t1.PAINTING_ID)
FROM ARTIST t0 JOIN PAINTING t1 ON (t0.ARTIST_ID = t1.ARTIST_ID)
WHERE t0.ARTIST_NAME LIKE ?
GROUP BY t0.ARTIST_NAME, t0.ARTIST_ID, t0.DATE_OF_BIRTH
HAVING COUNT(t1.PAINTING_ID) < ?
ORDER BY COUNT(t1.PAINTING_ID) DESC, t0.ARTIST_NAME
```

EJBQLQuery

EJBQLQuery was created as a part of an experiment in adopting some of Java Persistence API (JPA) approaches in Cayenne. It is a parameterized object query that is created from query String. A String used to build EJBQLQuery must conform to JPQL (JPA query language):

```
EJBQLQuery query = new EJBQLQuery("select a FROM Artist a");
```

JPQL details can be found in any JPA manual. Here we'll mention only how this fits into Cayenne and what are the differences between EJBQL and other Cayenne queries.

Although most frequently EJBQLQuery is used as an alternative to SelectQuery, there are also DELETE and UPDATE varieties available.



As of this version of Cayenne, DELETE and UPDATE do not change the state of objects in the ObjectContext. They are run directly against the database instead.

```
EJBQLQuery select = new EJBQLQuery("select a FROM Artist a WHERE a.name = 'Salvador Dali'");
List<Artist> artists = context.performQuery(select);
```

```
EJBQLQuery delete = new EJBQLQuery("delete from Painting");
context.performGenericQuery(delete);
```

```
EJBQLQuery update = new EJBQLQuery("UPDATE Painting AS p SET p.name = 'P2' WHERE
p.name = 'P1'");
context.performGenericQuery(update);
```

In most cases `SelectQuery` is preferred to `EJBQLQuery`, as it is API-based, and provides you with better compile-time checks. However sometimes you may want a completely scriptable object query. This is when you might prefer EJBQL. A more practical reason for picking EJBQL over `SelectQuery` though is that the former offers some extra selecting capabilities, namely aggregate functions and subqueries:

```
EJBQLQuery query = new EJBQLQuery("select a, COUNT(p) FROM Artist a JOIN a.paintings p
GROUP BY a");
List<Object[]> result = context.performQuery(query);
for(Object[] artistWithCount : result) {
    Artist a = (Artist) artistWithCount[0];
    int hasPaintings = (Integer) artistWithCount[1];
}
```

This also demonstrates a previously unseen type of select result - a List of `Object[]` elements, where each entry in an `Object[]` is either a `DataObject` or a scalar, depending on the query `SELECT` clause. A result can also be a list of scalars:

```
EJBQLQuery query = new EJBQLQuery("select a.name FROM Artist a");
List<String> names = context.performQuery(query);
```

`EJBQLQuery` supports an "IN" clause with three different usage-patterns. The following example would require three individual positional parameters (named parameters could also have been used) to be supplied.

```
select p from Painting p where p.paintingTitle in (?1,?2,?3)
```

The following example requires a single positional parameter to be supplied. The parameter can be any concrete implementation of the `java.util.Collection` interface such as `java.util.List` or `java.util.Set`.

```
select p from Painting p where p.paintingTitle in ?1
```

The following example is functionally identical to the one prior.

```
select p from Painting p where p.paintingTitle in (?1)
```

It is possible to convert an `Expression` object used with a `SelectQuery` to EJBQL. Use the `Expression#appendAsEJBQL` methods for this purpose.

While Cayenne Expressions discussed previously can be thought of as identical to JPQL WHERE clause, and indeed they are very close, there are a few notable differences:

- Null handling: `SelectQuery` would translate the expressions matching NULL values to the corresponding "X IS NULL" or "X IS NOT NULL" SQL syntax. `EJBQLQuery` on the other hand requires explicit "IS NULL" (or "IS NOT NULL") syntax to be used, otherwise the generated SQL will look like "X = NULL" (or "X <> NULL"), which will evaluate differently.
- Expression Parameters: `SelectQuery` uses "\$" to denote named parameters (e.g. "\$myParam"), while `EJBQL` uses ":" (e.g. ":myParam"). Also `EJBQL` supports positional parameters denoted by the question mark: "?3".

SelectById

This query allows to search objects by their ID. It's introduced in Cayenne 4.0 and uses new "fluent" API same as `ObjectSelect` query.

Here is example of how to use it:

```
Artist artistWithId1 = SelectById.query(Artist.class, 1)
    .prefetch(Artist.PAINTING_ARRAY.joint())
    .localCache()
    .selectOne(context);
```

SQLSelect and SQLExec

`SQLSelect` and `SQLExec` are essentially a "fluent" versions of older `SQLTemplate` query. `SQLSelect` can be used (as name suggests) to select custom data in form of entities, separate columns or collection of `DataRow`. `SQLExec` is designed to just execute any raw SQL code (e.g. updates, deletes, DDLs, etc.) This queries support all directives described in `SQLTemplate` section.

Here is example of how to use `SQLSelect`:

```
SQLSelect<Painting> q1 = SQLSelect
    .query(Painting.class, "SELECT * FROM PAINTING WHERE PAINTING_TITLE LIKE
#bind($title)")
    .params("title", "painting%")
    .upperColumnNames()
    .localCache()
    .limit(100)
    .select(context);
```

And here is example of how to use `SQLExec`:

```
int inserted = SQLExec
    .query("INSERT INTO ARTIST (ARTIST_ID, ARTIST_NAME) VALUES (#bind($id),
#bind($name))")
    .paramsArray(55, "Picasso")
    .update(context);
```

MappedSelect and MappedExec

`MappedSelect` and `MappedExec` is a queries that are just a reference to another queries stored in the `DataMap`. The actual stored query can be `SelectQuery`, `SQLTemplate`, `EJBQLQuery`, etc. Difference between `MappedSelect` and `MappedExec` is (as reflected in their names) whether underlying query intended to select data or just to perform some generic SQL code.



These queries are "fluent" versions of deprecated `NamedQuery` class.

Here is example of how to use `MappedSelect`:

```
List<Artist> results = MappedSelect.query("artistsByName", Artist.class)
    .param("name", "Picasso")
    .select(context);
```

And here is example of `MappedExec`:

```
QueryResult result = MappedExec.query("updateQuery")
    .param("var", "value")
    .execute(context);
System.out.println("Rows updated: " + result.firstUpdateCount());
```

ProcedureCall

Stored procedures are mapped as separate objects in `CayenneModeler`. `ProcedureCall` provides a way to execute them with a certain set of parameters. This query is a "fluent" version of older `ProcedureQuery`. Just like with `SQLTemplate`, the outcome of a procedure can be anything - a single result set, multiple result sets, some data modification (returned as an update count), or a combination of these. So use root class to get a single result set, and use only procedure name for anything else:

```
List<Artist> result = ProcedureCall.query("my_procedure", Artist.class)
    .param("p1", "abc")
    .param("p2", 3000)
    .call(context)
    .firstList();
```

```
// here we do not bother with root class.
// Procedure name gives us needed routing information
ProcedureResult result = ProcedureCall.query("my_procedure")
    .param("p1", "abc")
    .param("p2", 3000)
    .call();
```

A stored procedure can return data back to the application as result sets or via OUT parameters. To simplify the processing of the query output, QueryResponse treats OUT parameters as if it was a separate result set. For stored procedures declare any OUT or INOUT parameters, `ProcedureResult` have convenient utility method to get them:

```
ProcedureResult result = ProcedureCall.query("my_procedure")
    .call(context);

// read OUT parameters
Object out = result.getOutParam("out_param");
```

There maybe a situation when a stored procedure handles its own transactions, but an application is configured to use Cayenne-managed transactions. This is obviously conflicting and undesirable behavior. In this case ProcedureQueries should be executed explicitly wrapped in an "external" Transaction. This is one of the few cases when a user should worry about transactions at all. See Transactions section for more details.

Custom Queries

If a user needs some extra functionality not addressed by the existing set of Cayenne queries, he can write his own. The only requirement is to implement `org.apache.cayenne.query.Query` interface. The easiest way to go about it is to subclass some of the base queries in Cayenne.

E.g. to do something directly in the JDBC layer, you might subclass `AbstractQuery`:

```

public class MyQuery extends AbstractQuery {

    @Override
    public SQLAction createSQLAction(SQLActionVisitor visitor) {
        return new SQLAction() {

            @Override
            public void performAction(Connection connection, OperationObserver
observer) throws SQLException, Exception {
                // 1. do some JDBC work using provided connection...
                // 2. push results back to Cayenne via OperationObserver
            }
        };
    }
}

```

To delegate the actual query execution to a standard Cayenne query, you may subclass `IndirectQuery`:

```

public class MyDelegatingQuery extends IndirectQuery {

    @Override
    protected Query createReplacementQuery(EntityResolver resolver) {
        SQLTemplate delegate = new SQLTemplate(SomeClass.class, generateRawSQL());
        delegate.setFetchingDataRows(true);
        return delegate;
    }

    protected String generateRawSQL() {
        // build some SQL string
    }
}

```

In fact many internal Cayenne queries are `IndirectQueries`, delegating to `SelectQuery` or `SQLTemplate` after some preprocessing.

SQLTemplate

`SQLTemplate` is a query that allows to run native SQL from a Cayenne application. It comes handy when the standard ORM concepts are not sufficient for a given query or an update. SQL is too powerful and allows to manipulate data in ways that are not easily described as a graph of related entities. Cayenne acknowledges this fact and provides this facility to execute SQL, mapping the result to objects when possible. Here are examples of selecting and non-selecting `SQLTemplates`:

```

SQLTemplate select = new SQLTemplate(Artist.class, "select * from ARTIST");
List<Artist> result = context.performQuery(select);

```

```
SQLTemplate update = new SQLTemplate(Artist.class, "delete from ARTIST");
QueryResponse response = context.performGenericQuery(update);
```

Cayenne doesn't make any attempt to make sense of the SQL semantics, so it doesn't know whether a given query is performing a select or update, etc. It is the user's decision to run a given query as a selecting or "generic".



Any data modifications done to DB as a result of SQLTemplate execution do not change the state of objects in the ObjectContext. So some objects in the context may become stale as a result.

Another point to note is that the first argument to the SQLTemplate constructor - the Java class - has the same meaning as in SelectQuery only when the result can be converted to objects (e.g. when this is a selecting query and it is selecting all columns from one table). In this case it denotes the "root" entity of this query result. If the query does not denote a single entity result, this argument is only used for query routing, i.e. determining which database it should be run against. You are free to use any persistent class or even a DataMap instance in such situation. It will work as long as the passed "root" maps to the same database as the current query.

To achieve interoperability between multiple RDBMS a user can specify multiple SQL statements for the same SQLTemplate, each corresponding to a native SQL dialect. A key used to look up the right dialect during execution is a fully qualified class name of the corresponding DbAdapter. If no DB-specific statement is present for a given DB, a default generic statement is used. E.g. in all the examples above a default statement will be used regardless of the runtime database. So in most cases you won't need to explicitly "translate" your SQL to all possible dialects. Here is how this works in practice:

```
SQLTemplate select = new SQLTemplate(Artist.class, "select * from ARTIST");

// For Postgres it would be nice to trim padding of all CHAR columns.
// Otherwise those will be returned with whitespace on the right.
// assuming "NAME" is defined as CHAR...
String pgSQL = "SELECT ARTIST_ID, RTRIM(NAME), DATE_OF_BIRTH FROM ARTIST";
query.setTemplate(PostgresAdapter.class.getName(), pgSQL);
```

Scripting SQLTemplate with Velocity

The most interesting aspect of SQLTemplate (and the reason why it is called a "template") is that a SQL string is treated by Cayenne as an Apache Velocity template. Before sending it to DB as a PreparedStatement, the String is evaluated in the Velocity context, that does variable substitutions, and performs special callbacks in response to various directives, thus controlling query interaction with the JDBC layer.

Check Velocity docs for the syntax details. Here we'll just mention the two main scripting elements - "variables" (that look like `$var`) and "directives" (that look like `#directive(p1 p2 p3)`). All built-in Velocity directives are supported. Additionally Cayenne defines a number of its own directives to bind parameters to PreparedStatements and to control the structure of the ResultSet. These

directives are described in the following sections.

Variable Substitution

All variables in the template string are replaced from query parameters:

```
SQLTemplate query = new SQLTemplate(Artist.class, "delete from $tableName");
query.setParameters(Collections.singletonMap("tableName", "mydb.PAINTING"));

// this will generate SQL like this: "delete from mydb.PAINTING"
```

The example above demonstrates the point made earlier in this chapter - even if we don't know upfront which table the query will run against, we can still use a fixed "root" in constructor (`Artist.class` in this case), as we are not planning on converting the result to objects.

Variable substitution within the text uses `"object.toString()"` method to replace the variable value. Keep in mind that this may not be appropriate in all situations. E.g. passing a date object in a WHERE clause expression may be converted to a String not understood by the target RDBMS SQL parser. In such cases variable should be wrapped in `#bind` directive as described below.

Directives

These are the Cayenne directives used to customize SQLTemplate parsing and integrate it with the JDBC layer:

#bind

Creates a PreparedStatement positional parameter in place of the directive, binding the value to it before statement execution. `#bind` is allowed in places where a "?" would be allowed in a PreparedStatement. And in such places it almost always makes sense to pass objects to the template via this or other forms of `#bind` instead of inserting them inline.

Semantics:

```
#bind(value)
#bind(value jdbcType)
#bind(value jdbcType scale)
```

Arguments:

- `value` - can either be a char constant or a variable that is resolved from the query parameters. Note that the variable can be a collection, that will be automatically expanded into a list of individual value bindings. This is useful for instance to build IN conditions.
- `jdbcType` - is a JDBC data type of the parameter as defined in `java.sql.Types`.
- `scale` - An optional scale of the numeric value. Same as "scale" in PreparedStatement.

Usage:

```
#bind($xyz)
#bind('str')
#bind($xyz 'VARCHAR')
#bind($xyz 'DECIMAL' 2)
```

Full example:

```
update ARTIST set NAME = #bind($name) where ID = #bind($id)
```

#bindEqual

Same as #bind, but also includes the "=" sign in front of the value binding. Look at the example below - we took the #bind example and replaced "ID = #bind(..)" with "ID #bindEqual(..)". While it looks like a clumsy shortcut to eliminate the equal sign, the actual reason why this is useful is that it allows the value to be null. If the value is not null, "= ?" is generated, but if it is, the resulting chunk of the SQL would look like "IS NULL" and will be compliant with what the DB expects.

Semantics:

```
#bindEqual(value)
#bindEqual(value jdbcType)
#bindEqual(value jdbcType scale)
```

Arguments: (same as #bind)

Usage:

```
#bindEqual($xyz)
#bindEqual('str')
#bindEqual($xyz 'VARCHAR')
#bindEqual($xyz 'DECIMAL' 2)
```

Full example:

```
update ARTIST set NAME = #bind($name) where ID #bindEqual($id)
```

#bindNotEqual

This directive deals with the same issue as #bindEqual above, only it generates "not equal" in front of the value (or IS NOT NULL).

Semantics:

```
#bindNotEqual(value)
#bindNotEqual(value jdbcType)
#bindNotEqual(value jdbcType scale)
```

Arguments: (same as #bind)

Usage:

```
#bindNotEqual($xyz)
#bindNotEqual('str')
#bindNotEqual($xyz 'VARCHAR')
#bindNotEqual($xyz 'DECIMAL' 2)
```

Full example:

```
update ARTIST set NAME = #bind($name) where ID #bindEqual($id)
```

#bindObjectEqual

It can be tricky to use a Persistent object or an ObjectId in a binding, especially for tables with compound primary keys. This directive helps to handle such binding. It maps columns in the query to the names of Persistent object ID columns, extracts ID values from the object, and generates SQL like "COL1 = ? AND COL2 = ? ..." , binding positional parameters to ID values. It can also correctly handle null object. Also notice how we are specifying a Velocity array for multi-column PK.

Semantics:

```
#bindObjectEqual(value columns idColumns)
```

Arguments:

- **value** - must be a variable that is resolved from the query parameters to a Persistent or ObjectId.
- **columns** - the names of the columns to generate in the SQL.
- **idColumn** - the names of the ID columns for a given entity. Must match the order of "columns" to match against.

Usage:

```
#bindObjectEqual($a 't0.ID' 'ID')
#bindObjectEqual($b ['t0.FK1', 't0.FK2'] ['PK1', 'PK2'])
```

Full example:

```
String sql = "SELECT * FROM PAINTING t0 WHERE #bindObjectEqual($a 't0.ARTIST_ID'
'ARTIST_ID' ) ORDER BY PAINTING_ID";
SQLTemplate select = new SQLTemplate(Artist.class, sql);

Artist a = ....
select.setParameters(Collections.singletonMap("a", a));
```

#bindObjectNotEqual

Same as #bindObjectEqual above, only generates "not equal" operator for value comparison (or IS NOT NULL).

Semantics:

```
#bindObjectNotEqual(value columns idColumns)
```

Arguments: (same as #bindObjectEqual)

Usage:

```
#bindObjectNotEqual($a 't0.ID' 'ID')
#bindObjectNotEqual($b ['t0.FK1', 't0.FK2'] ['PK1', 'PK2'])
```

Full example:

```
String sql = "SELECT * FROM PAINTING t0 WHERE #bindObjectNotEqual($a 't0.ARTIST_ID'
'ARTIST_ID' ) ORDER BY PAINTING_ID";
SQLTemplate select = new SQLTemplate(Artist.class, sql);

Artist a = ....
select.setParameters(Collections.singletonMap("a", a));
```

#result

Renders a column in SELECT clause of a query and maps it to a key in the result DataRow. Also ensures the value read is of the correct type. This allows to create a DataRow (and ultimately - a persistent object) from an arbitrary ResultSet.

Semantics:

```
#result(column)
#result(column javaType)
#result(column javaType alias)
#result(column javaType alias dataRowKey)
```

Arguments:

- **column** - the name of the column to render in SQL SELECT clause.
- **javaType** - a fully-qualified Java class name for a given result column. For simplicity most common Java types used in JDBC can be specified without a package. These include all numeric types, primitives, String, SQL dates, BigDecimal and BigInteger. So `"#result('A' 'String')"`, `"#result('B' 'java.lang.String')"` and `"#result('C' 'int')"` are all valid
- **alias** - specifies both the SQL alias of the column and the value key in the DataRow. If omitted, "column" value is used.
- **dataRowKey** - needed if SQL 'alias' is not appropriate as a DataRow key on the Cayenne side. One common case when this happens is when a DataRow retrieved from a query is mapped using joint prefetch keys (see below). In this case DataRow must use database path expressions for joint column keys, and their format is incompatible with most databases alias format.

Usage:

```
#result('NAME')
#result('DATE_OF_BIRTH' 'java.util.Date')
#result('DOB' 'java.util.Date' 'DATE_OF_BIRTH')
#result('DOB' 'java.util.Date' '' 'artist.DATE_OF_BIRTH')
#result('SALARY' 'float')
```

Full example:

```
SELECT #result('ID' 'int'), #result('NAME' 'String'), #result('DATE_OF_BIRTH'
'java.util.Date') FROM ARTIST
```

#chain and #chunk

#chain and **#chunk** directives are used for conditional inclusion of SQL code. They are used together with **#chain** wrapping multiple **#chunks**. A chunk evaluates its parameter expression and if it is NULL suppresses rendering of the enclosed SQL block. A chain renders its prefix and its chunks joined by the operator. If all the chunks are suppressed, the chain itself is suppressed. This allows to work with otherwise hard to script SQL semantics. E.g. a WHERE clause can contain multiple conditions joined with AND or OR. Application code would like to exclude a condition if its right-hand parameter is not present (similar to Expression pruning discussed above). If all conditions are excluded, the entire WHERE clause should be excluded. **#chain + #chunk** allows to do that.

Semantics:

```
#chain(operator) ... #end
  #chain(operator prefix) ... #end
  #chunk() ... #end
  #chunk(param) ... #end
  ...
```

Full example:

```
#chain('OR' 'WHERE')
    #chunk($name) NAME LIKE #bind($name) #end
    #chunk($id) ARTIST_ID > #bind($id) #end
#end"
```

Mapping SQLTemplate Results

Here we'll discuss how to convert the data selected via SQLTemplate to some useable format, compatible with other query results. It can either be very simple or very complex, depending on the structure of the SQL, JDBC driver nature and the desired result structure. This section presents various tips and tricks dealing with result mapping.

By default SQLTemplate is expected to return a List of Persistent objects of its root type. This is the simple case:

```
SQLTemplate query = new SQLTemplate(Artist.class, "SELECT * FROM ARTIST");

// List of Artists
List<Artist> artists = context.performQuery(query);
```

Just like SelectQuery, SQLTemplate can fetch DataRows. In fact DataRows option is very useful with SQLTemplate, as the result type most often than not does not represent a Cayenne entity, but instead may be some aggregated report or any other data whose object structure is opaque to Cayenne:

```
String sql = "SELECT t0.NAME, COUNT(1) FROM ARTIST t0 JOIN PAINTING t1 ON (t0.ID = t1.ARTIST_ID) "
    + "GROUP BY t0.NAME ORDER BY COUNT(1)";
SQLTemplate query = new SQLTemplate(Artist.class, sql);

// ensure we are fetching DataRows
query.setFetchingDataRows(true);

// List of DataRow
List<DataRow> rows = context.performQuery(query);
```

In the example above, even though the query root is Artist. the result is a list of artist names with painting counts (as mentioned before in such case "root" is only used to find the DB to fetch against, but has no bearing on the result). The DataRows here are the most appropriate and desired result type.

In a more advanced case you may decide to fetch a list of scalars or a list of Object[] with each array entry being either an entity or a scalar. You probably won't be doing this too often and it requires quite a lot of work to setup, but if you want your SQLTemplate to return results similar to EJSQLQuery, it is doable using SQLResult as described below:

```
SQLTemplate query = new SQLTemplate(Painting.class, "SELECT ESTIMATED_PRICE P FROM PAINTING");
```

```
// let Cayenne know that result is a scalar  
SQLResult resultDescriptor = new SQLResult();  
resultDescriptor.addColumnResult("P");  
query.setResult(resultDescriptor);
```

```
// List of BigDecimals  
List<BigDecimal> prices = context.performQuery(query);
```

```
SQLTemplate query = new SQLTemplate(Artist.class, "SELECT t0.ID, t0.NAME, t0.DATE_OF_BIRTH, COUNT(t1.PAINTING_ID) C " +  
    "FROM ARTIST t0 LEFT JOIN PAINTING t1 ON (t0.ID = t1.ARTIST_ID) " +  
    "GROUP BY t0.ID, t0.NAME, t0.DATE_OF_BIRTH");
```

```
// let Cayenne know that result is a mix of Artist objects and the count of their paintings
```

```
EntityResult artistResult = new EntityResult(Artist.class);  
artistResult.addDbField(Artist.ID_PK_COLUMN, "ARTIST_ID");  
artistResult.addObjectField(Artist.NAME_PROPERTY, "NAME");  
artistResult.addObjectField(Artist.DATE_OF_BIRTH_PROPERTY, "DATE_OF_BIRTH");
```

```
SQLResult resultDescriptor = new SQLResult();  
resultDescriptor.addEntityResult(artistResult);  
resultDescriptor.addColumnResult("C");  
query.setResult(resultDescriptor);
```

```
// List of Object[]  
List<Object[]> data = context.performQuery(query);
```

Another trick related to mapping result sets is making Cayenne recognize prefetched entities in the result set. This emulates "joint" prefetching of SelectQuery, and is achieved by special column naming. Columns belonging to the "root" entity of the query should use unqualified names corresponding to the root DbEntity columns. For each related entity column names must be prefixed with relationship name and a dot (e.g. "toArtist.ID"). Column naming can be controlled with "#result" directive:

```
String sql = "SELECT distinct "
    + "#result('t1.ESTIMATED_PRICE' 'BigDecimal' '' 'paintings.ESTIMATED_PRICE'), "
    + "#result('t1.PAINTING_TITLE' 'String' '' 'paintings.PAINTING_TITLE'), "
    + "#result('t1.GALLERY_ID' 'int' '' 'paintings.GALLERY_ID'), "
    + "#result('t1.ID' 'int' '' 'paintings.ID'), "
    + "#result('NAME' 'String'), "
    + "#result('DATE_OF_BIRTH' 'java.util.Date'), "
    + "#result('t0.ID' 'int' '' 'ID') "
    + "FROM ARTIST t0, PAINTING t1 "
    + "WHERE t0.ID = t1.ARTIST_ID";
```

```
SQLTemplate q = new SQLTemplate(Artist.class, sql);
q.addPrefetch(Artist.PAINTINGS_PROPERTY)
List<Artist> objects = context.performQuery(query);
```

And the final tip deals with capitalization of the DataRow keys. Queries like `"SELECT * FROM..."` and even `"SELECT COLUMN1, COLUMN2, ... FROM ..."` can sometimes result in Cayenne exceptions on attempts to convert fetched DataRows to objects. Essentially any query that is not using a `#result` directive to describe the result set is prone to this problem, as different databases may produce different capitalization of the `java.sql.ResultSet` columns.

The most universal way to address this issue is to describe each column explicitly in the `SQLTemplate` via `#result`, e.g.: `"SELECT #result('column1'), #result('column2'), .."`. However this quickly becomes impractical for tables with lots of columns. For such cases Cayenne provides a shortcut based on the fact that an ORM mapping usually follows some naming convention for the column names. Simply put, for case-insensitive databases developers normally use either all lowercase or all uppercase column names. Here is the API that takes advantage of that user knowledge and forces Cayenne to follow a given naming convention for the DataRow keys (this is also available as a dropdown in the Modeler):

```
SQLTemplate query = new SQLTemplate("SELECT * FROM ARTIST");
query.setColumnNamesCapitalization(CapsStrategy.LOWER);
List objects = context.performQuery(query);
```

or

```
SQLTemplate query = new SQLTemplate("SELECT * FROM ARTIST");
query.setColumnNamesCapitalization(CapsStrategy.UPPER);
List objects = context.performQuery(query);
```

None of this affects the generated SQL, but the resulting DataRows are using correct capitalization. Note that you probably shouldn't bother with this unless you are getting `CayenneRuntimeExceptions` when fetching with `SQLTemplate`.

2.7. Lifecycle Events

An application might be interested in getting notified when a Persistent object moves through its lifecycle (i.e. fetched from DB, created, modified, committed). E.g. when a new object is created, the application may want to initialize its default properties (this can't be done in constructor, as constructor is also called when an object is fetched from DB). Before save, the application may perform validation and/or set some properties (e.g. "updatedAtTimestamp"). After save it may want to create an audit record for each saved object, etc., etc.

All this can be achieved by declaring callback methods either in Persistent objects or in non-persistent listener classes defined by the application (further simply called "listeners"). There are eight types of lifecycle events supported by Cayenne, listed later in this chapter. When any such event occurs (e.g. an object is committed), Cayenne would invoke all appropriate callbacks. Persistent objects would receive their own events, while listeners would receive events from any objects.

Cayenne allows to build rather powerful and complex "workflows" or "processors" tied to objects lifecycle, especially with listeners, as they have full access to the application environment outside Cayenne. This power comes from such features as filtering which entity events are sent to a given listener and the ability to create a common operation context for multiple callback invocations. All of these are discussed later in this chapter.

Types of Lifecycle Events

Cayenne defines the following 8 types of lifecycle events for which callbacks can be registered:

Table 12. Lifecycle Event Types

Event	Occurs...
PostAdd	right after a new object is created inside <code>ObjectContext.newObject()</code> . When this event is fired the object is already registered with its <code>ObjectContext</code> and has its <code>ObjectId</code> and <code>ObjectContext</code> properties set.
PrePersist	right before a new object is committed, inside <code>ObjectContext.commitChanges()</code> and <code>ObjectContext.commitChangesToParent()</code> (and after " <code>validateForInsert()</code> ").
PreUpdate	right before a modified object is committed, inside <code>ObjectContext.commitChanges()</code> and <code>ObjectContext.commitChangesToParent()</code> (and after " <code>validateForUpdate()</code> ").
PreRemove	right before an object is deleted, inside <code>ObjectContext.deleteObjects()</code> . The event is also generated for each object indirectly deleted as a result of CASCADE delete rule.
PostPersist	right after a commit of a new object is done, inside <code>ObjectContext.commitChanges()</code> .
PostUpdate	right after a commit of a modified object is done, inside <code>ObjectContext.commitChanges()</code> .
PostRemove	right after a commit of a deleted object is done, inside <code>ObjectContext.commitChanges()</code> .

Event	Occurs...
PostLoad	<ul style="list-style-type: none"> • After an object is fetched inside <code>ObjectContext.performQuery()</code>. • After an object is reverted inside <code>ObjectContext.rollbackChanges()</code>. • Anytime a faulted object is resolved (i.e. if a relationship is fetched).

Callbacks on Persistent Objects

Callback methods on Persistent classes are mapped in `CayenneModeler` for each `ObjEntity`. Empty callback methods are automatically created as a part of class generation (either with Maven, Ant or the Modeler) and are later filled with appropriate logic by the programmer. E.g. assuming we mapped a 'post-add' callback called 'onNewOrder' in `ObjEntity` 'Order', the following code will be generated:

```
public abstract class _Order extends CayenneDataObject {
    protected abstract void onNewOrder();
}

public class Order extends _Order {

    @Override
    protected void onNewOrder() {
        //TODO: implement onNewOrder
    }
}
```

As `onNewOrder()` is already declared in the mapping, it does not need to be registered explicitly. Implementing the method in subclass to do something meaningful is all that is required at this point.

As a rule callback methods do not have any knowledge of the outside application, and can only access the state of the object itself and possibly the state of other persistent objects via object's own `ObjectContext`.



Validation and callbacks: There is a clear overlap in functionality between object callbacks and `DataObject.validateForX()` methods. In the future validation may be completely superceded by callbacks. It is a good idea to use "validateForX" strictly for validation (or not use it at all). Updating the state before commit should be done via callbacks.

Callbacks on Non-Persistent Listeners

A listener is simply some application class that has one or more annotated callback methods. A callback method signature should be `void someMethod(SomePersistentType object)`. It can be public, private, protected or use default access:

```

public class OrderListener {

    @PostAdd(Order.class)
    public void setDefaultsForNewOrder(Order o) {
        o.setCreatedOn(new Date());
    }
}

```

Notice that the example above contains an annotation on the callback method that defines the type of the event this method should be called for. Before we go into annotation details, we'll show how to create and register a listener with Cayenne. It is always a user responsibility to register desired application listeners, usually right after `ServerRuntime` is started. Here is an example:

First let's define 2 simple listeners.

```

public class Listener1 {

    @PostAdd(MyEntity.class)
    void postAdd(Persistent object) {
        // do something
    }
}

public class Listener2 {

    @PostRemove({ MyEntity1.class, MyEntity2.class })
    void postRemove(Persistent object) {
        // do something
    }

    @PostUpdate({ MyEntity1.class, MyEntity2.class })
    void postUpdate(Persistent object) {
        // do something
    }
}

```

Ignore the annotations for a minute. The important point here is that the listeners are arbitrary classes unmapped and unknown to Cayenne, that contain some callback methods. Now let's register them with runtime:

```

ServerRuntime runtime = ServerRuntime.builder()
    // ..
    .addModule(binder ->
        ServerModule.contributeDomainListeners()
            .add(new Listener1())
            .add(new Listener2())
    )
    // ..
    .build();

```

Listeners in this example are very simple. However they don't have to be. Unlike Persistent objects, normally listeners initialization is managed by the application code, not Cayenne, so listeners may have knowledge of various application services, operation transactional context, etc. Besides a single listener can apply to multiple entities. As a consequence their callbacks can do more than just access a single `ObjectContext`.

Now let's discuss the annotations. There are eight annotations exactly matching the names of eight lifecycle events. A callback method in a listener should be annotated with at least one, but possibly with more than one of them. Annotation itself defines what event the callback should react to. Annotation parameters are essentially an entity filter, defining a subset of `ObjEntities` whose events we are interested in:

```

// this callback will be invoked on PostRemove event of any object
// belonging to MyEntity1, MyEntity2 or their subclasses
@PostRemove({ MyEntity1.class, MyEntity2.class })
void postRemove(Persistent object) {
    ...
}

```

```

// similar example with multiple annotations on a single method
// each matching just one entity
@PostPersist(MyEntity1.class)
@PostRemove(MyEntity1.class)
@PostUpdate(MyEntity1.class)
void postCommit(MyEntity1 object) {
    ...
}

```

As shown above, "value" (the implicit annotation parameter) can contain one or more entity classes. Only these entities' events will result in callback invocation. There's also another way to match entities - via custom annotations. This allows to match any number of entities without even knowing what they are. Here is an example. We'll first define a custom annotation:

```

@Target(ElementType.TYPE)
@Retention(RetentionPolicy.RUNTIME)
public @interface Tag {

}

```

Now we can define a listener that will react to events from ObjEntities annotated with this annotation:

```

public class Listener3 {

    @PostAdd(entityAnnotations = Tag.class)
    void postAdd(Persistent object) {
        // do something
    }

}

```

As you see we don't have any entities yet, still we can define a listener that does something useful. Now let's annotate some entities:

```

@Tag
public class MyEntity1 extends _MyEntity1 {

}

@Tag
public class MyEntity2 extends _MyEntity2 {

}

```

Combining Listeners with DataChannelFilters

A final touch in the listeners design is preserving the state of the listener within a single select or commit, so that events generated by multiple objects can be collected and processed all together. To do that you will need to implement a **DataChannelFilter**, and add some callback methods to it. They will store their state in a ThreadLocal variable of the filter. Here is an example filter that does something pretty meaningless - counts how many total objects were committed. However it demonstrates the important pattern of aggregating multiple events and presenting a combined result:

```

public class CommittedObjectCounter implements DataChannelFilter {

    private ThreadLocal<int[]> counter;

    @Override
    public void init(DataChannel channel) {
        counter = new ThreadLocal<int[]>();
    }

    @Override
    public QueryResponse onQuery(ObjectContext originatingContext, Query query,
DataChannelFilterChain filterChain) {
        return filterChain.onQuery(originatingContext, query);
    }

    @Override
    public GraphDiff onSync(ObjectContext originatingContext, GraphDiff changes, int
syncType,
        DataChannelFilterChain filterChain) {

        // init the counter for the current commit
        counter.set(new int[1]);

        try {
            return filterChain.onSync(originatingContext, changes, syncType);
        } finally {

            // process aggregated result and release the counter
            System.out.println("Committed " + counter.get()[0] + " object(s)");
            counter.set(null);
        }
    }

    @PostPersist(entityAnnotations = Tag.class)
    @PostUpdate(entityAnnotations = Tag.class)
    @PostRemove(entityAnnotations = Tag.class)
    void afterCommit(Persistent object) {
        counter.get()[0]++;
    }
}

```

Now since this is both a filter and a listener, it needs to be registered as such:

```
// this will also add filter as a listener
ServerRuntime runtime = ServerRuntime.builder()
    // ..
    .addModule(b ->
        ServerModule.contributeDomainFilters(b)
            .add(CommittedObjectCounter.class)
    )
    // ..
    .build();
```

2.8. Performance Tuning

Prefetching

Prefetching is a technique that allows to bring back in one query not only the queried objects, but also objects related to them. In other words it is a controlled eager relationship resolving mechanism. Prefetching is discussed in the "Performance Tuning" chapter, as it is a powerful performance optimization method. However another common application of prefetching is to refresh stale object relationships, so more generally it can be viewed as a technique for managing subsets of the object graph.

Prefetching example:

```
ObjectSelect<Artist> query = ObjectSelect.query(Artist.class);

// instructs Cayenne to prefetch one of Artist's relationships
query.prefetch(Artist.PAINTINGS.disjoint());

// the above line is equivalent to the following:
// query.prefetch("paintings", PrefetchTreeNode.DISJOINT_PREFETCH_SEMANTICS);

// query is executed as usual, but the resulting Artists will have
// their paintings "inflated"
List<Artist> artists = query.select(context);
```

All types of relationships can be prefetched - to-one, to-many, flattened. A prefetch can span multiple relationships:

```
query.prefetch(Artist.PAINTINGS.dot(Painting.GALLERY).disjoint());
```

A query can have multiple prefetches:

```
query.prefetch(Artist.PAINTINGS.disjoint());
query.prefetch(Artist.PAINTINGS.dot(Painting.GALLERY).disjoint());
```

If a query is fetching DataRows, all "disjoint" prefetches are ignored, only "joint" prefetches are executed (see prefetching semantics discussion below for what disjoint and joint prefetches mean).

Prefetching Semantics

Prefetching semantics defines a strategy to prefetch relationships. Depending on it, Cayenne would generate different types of queries. The end result is the same - query root objects with related objects fully resolved. However semantics can affect performance, in some cases significantly. There are 3 types of prefetch semantics, all defined as constants in `org.apache.cayenne.query.PrefetchTreeNode`:

```
PrefetchTreeNode.JOINT_PREFETCH_SEMANTICS  
PrefetchTreeNode.DISJOINT_PREFETCH_SEMANTICS  
PrefetchTreeNode.DISJOINT_BY_ID_PREFETCH_SEMANTICS
```

There's no limitation on mixing different types of semantics in the same query. Each prefetch can have its own semantics. `SelectQuery` uses `DISJOINT_PREFETCH_SEMANTICS` by default. `ObjectSelect` requires explicit semantics as we've seen above. `SQLTemplate` and `ProcedureQuery` are both using `JOINT_PREFETCH_SEMANTICS` and it can not be changed due to the nature of those two queries.

Disjoint Prefetching Semantics

This semantics results in Cayenne generating one SQL statement for the main objects, and a separate statement for each prefetch path (hence "disjoint" - related objects are not fetched with the main query). Each additional SQL statement uses a qualifier of the main query plus a set of joins traversing the prefetch path between the main and related entity.

This strategy has an advantage of efficient JVM memory use, and faster overall result processing by Cayenne, but it requires $(1+N)$ SQL statements to be executed, where N is the number of prefetched relationships.

Disjoint-by-ID Prefetching Semantics

This is a variation of disjoint prefetch where related objects are matched against a set of IDs derived from the fetched main objects (or intermediate objects in a multi-step prefetch). Cayenne limits the size of the generated WHERE clause, as most DBs can't parse arbitrary large SQL. So prefetch queries are broken into smaller queries. The size of is controlled by the DI property `Constants.SERVER_MAX_ID_QUALIFIER_SIZE_PROPERTY` (the default number of conditions in the generated WHERE clause is 10000). Cayenne will generate $(1 + N * M)$ SQL statements for each query using disjoint-by-ID prefetches, where N is the number of relationships to prefetch, and M is the number of queries for a given prefetch that is dependent on the number of objects in the result (ideally $M = 1$).

The advantage of this type of prefetch is that matching database rows by ID may be much faster than matching the qualifier of the original query. Moreover this is **the only type of prefetch** that can handle `SelectQueries` with `fetch` limit. Both joint and regular disjoint prefetches may produce invalid results or generate inefficient fetch-the-entire table SQL when fetch limit is in effect.

The disadvantage is that query SQL can get unwieldy for large result sets, as each object will have

to have its own condition in the WHERE clause of the generated SQL.

Joint Prefetching Semantics

Joint semantics results in a single SQL statement for root objects and any number of jointly prefetched paths. Cayenne processes in memory a cartesian product of the entities involved, converting it to an object tree. It uses OUTER joins to connect prefetched entities.

Joint is the most efficient prefetch type of the three as far as generated SQL goes. There's always just 1 SQL query generated. Its downsides are the potentially increased amount of data that needs to get across the network between the application server and the database, and more data processing that needs to be done on the Cayenne side.

Similar Behaviours Using EJBQL

It is possible to achieve similar behaviours with [EJBQLQuery](#) queries by employing the "FETCH" keyword.

```
SELECT a FROM Artist a LEFT JOIN FETCH a.paintings
```

In this case, the Paintings that exist for the Artist will be obtained at the same time as the Artists are fetched. Refer to third-party query language documentation for further detail on this mechanism.

Data Rows

Converting result set data to Persistent objects and registering these objects in the ObjectContext can be an expensive operation comparable to the time spent running the query (and frequently exceeding it). Internally Cayenne builds the result as a list of DataRows, that are later converted to objects. Skipping the last step and using data in the form of DataRows can significantly increase performance.

DataRow is a simply a map of values keyed by their DB column name. It is a ubiquitous representation of DB data used internally by Cayenne. And it can be quite usable as is in the application in many cases. So performance sensitive selects should consider DataRows - it saves memory and CPU cycles. All selecting queries support DataRows option, e.g.:

```
ObjectSelect<DataRow> query = ObjectSelect.dataRowQuery(Artist.class);  
  
List<DataRow> rows = query.select(context);
```

```
SQLSelect<DataRow> query = SQLSelect.dataRowQuery("SELECT * FROM ARTIST");  
List<DataRow> rows = query.select(context);
```

Individual DataRows may be converted to Persistent objects as needed. So e.g. you may implement some in-memory filtering, only converting a subset of fetched objects:

```
// you need to cast ObjectContext to DataContext to get access to 'objectFromDataRow'
DataContext dataContext = (DataContext) context;

for(DataRow row : rows) {
    if(row.get("DATE_OF_BIRTH") != null) {
        Artist artist = dataContext.objectFromDataRow(Artist.class, row);
        // do something with Artist...
        ...
    }
}
```

Specific Attributes and Relationships with EJBQL

It is possible to fetch specific attributes and relationships from a model using [EJBQLQuery](#). The following example would return a `java.util.List` of `String` objects;

```
SELECT a.name FROM Artist a
```

The following will yield a `java.util.List` containing `Object[]` instances, each of which would contain the name followed by the `dateOfBirth` value.

```
SELECT a.name, a.dateOfBirth FROM Artist a
```

Refer to third-party query language documentation for further detail on this mechanism.

Iterated Queries

While contemporary hardware may easily allow applications to fetch hundreds of thousands or even millions of objects into memory, it doesn't mean this is always a good idea to do so. You can optimize processing of very large result sets with two techniques discussed in this and the following chapter - iterated and paginated queries.

Iterated query is not actually a special query. Any selecting query can be executed in iterated mode by an `ObjectContext`. `ObjectContext` creates an object called `ResultIterator` that is backed by an open `ResultSet`. `Iterator` provides constant memory performance for arbitrarily large `ResultSets`. This is true at least on the Cayenne end, as JDBC driver may still decide to bring the entire `ResultSet` into the JVM memory.

Data is read from `ResultIterator` one row/object at a time until it is exhausted. There are two styles of accessing `ResultIterator` - direct access which requires explicit closing to avoid JDBC resources leak, or a callback that lets Cayenne handle resource management. In both cases iteration can be performed using "for" loop, as `ResultIterator` is "Iterable".

Direct access. Here common sense tells us that `ResultIterators` instances should be processed and closed as soon as possible to release the DB connection. E.g. storing open iterators between HTTP requests for unpredictable length of time would quickly exhaust the connection pool.

```
try(ResultIterator<Artist> it = ObjectSelect.query(Artist.class).iterator(context)) {
    for(Artist a : it) {
        // do something with the object...
        ...
    }
}
```

Same thing with a callback:

```
ObjectSelect.query(Artist.class).iterate(context, (Artist a) -> {
    // do something with the object...
    ...
});
```

Another example is a batch iterator that allows to process more than one object in each iteration. This is a common scenario in various data processing jobs - read a batch of objects, process them, commit the results, and then repeat. This allows to further optimize processing (e.g. by avoiding frequent commits).

```
try(ResultBatchIterator<Artist> it = ObjectSelect.query(Artist.class).batchIterator(
    context, 100)) {
    for(List<Artist> list : it) {
        // do something with each list
        ...
        // possibly commit your changes
        context.commitChanges();
    }
}
```

Paginated Queries

Enabling query pagination allows to load very large result sets in a Java app with very little memory overhead (much smaller than even the DataRows option discussed above). Moreover it is completely transparent to the application - a user gets what appears to be a list of Persistent objects - there's no iterator to close or DataRows to convert to objects:

```
// the fact that result is paginated is transparent
List<Artist> artists =
    ObjectSelect.query(Artist.class).pageSize(50).select(context);
```

Having said that, DataRows option can be combined with pagination, providing the best of both worlds:

```
List<DataRow> rows =  
    ObjectSelect.dataRowQuery(Artist.class).pageSize(50).select(context);
```

The way pagination works internally, it first fetches a list of IDs for the root entity of the query. This is very fast and initially takes very little memory. Then when an object is requested at an arbitrary index in the list, this object and adjacent objects (a "page" of objects that is determined by the query `pageSize` parameter) are fetched together by ID. Subsequent requests to the objects of this "page" are served from memory.

An obvious limitation of pagination is that if you eventually access all objects in the list, the memory use will end up being the same as with no pagination. However it is still a very useful approach. With some lists (e.g. multi-page search results) only a few top objects are normally accessed. At the same time pagination allows to estimate the full list size without fetching all the objects. And again - it is completely transparent and looks like a normal query.

Caching and Fresh Data

Object Caching

Query Result Caching

Cayenne supports mostly transparent caching of the query results. There are two levels of the cache: local (i.e. results cached by the `ObjectContext`) and shared (i.e. the results cached at the stack level and shared between all contexts). Local cache is much faster than the shared one, but is limited to a single context. It is often used with a shared read-only `ObjectContext`.

To take advantage of query result caching, the first step is to mark your queries appropriately. Here is an example for `ObjectSelect` query. Other types of queries have similar API:

```
ObjectSelect.query(Artist.class).localCache("artists");
```

This tells Cayenne that the query created here would like to use local cache of the context it is executed against. A vararg parameter to `localCache()` (or `sharedCache()`) method contains so called "cache groups". Those are arbitrary names that allow to categorize queries for the purpose of setting cache policies or explicit invalidation of the cache. More on that below.

The above API is enough for the caching to work, but by default your cache is an unmanaged LRU map. You can't control its size, expiration policies, etc. For the managed cache, you will need to explicitly use one of the more advanced cache providers. Use can use [JCache integration module](#) to enable any of JCache API compatible caching providers.

Often "passive" cache expiration policies used by caching providers are not sufficient, and the users want real-time cache invalidation when the data changes. So in addition to those policies, the app can invalidate individual cache groups explicitly with `RefreshQuery`:

```
RefreshQuery refresh = new RefreshQuery("artist");
context.performGenericQuery(refresh);
```

The above can be used e.g. to build UI for manual cache invalidation. It is also possible to automate cache refresh when certain entities are committed. This can be done with the help of [Cache invalidation extension](#).

Finally you may cluster cache group events. They are very small and can be efficiently sent over the wire to other JVMs running Cayenne. An example of Cayenne setup with event clustering is [available on GitHub](#).

Turning off Synchronization of ObjectContexts

By default when a single ObjectContext commits its changes, all other contexts in the same runtime receive an event that contains all the committed changes. This allows them to update their cached object state to match the latest committed data. There are however many problems with this ostensibly helpful feature. In short - it works well in environments with few contexts and in unclustered scenarios, such as single user desktop applications, or simple webapps with only a few users. More specifically:

- The performance of synchronization is (probably worse than) $O(N)$ where N is the number of peer ObjectContexts in the system. In a typical webapp N can be quite large. Besides for any given context, due to locking on synchronization, context own performance will depend not only on the queries that it runs, but also on external events that it does not control. This is unacceptable in most situations.
- Commit events are untargeted - even contexts that do not hold a given updated object will receive the full event that they will have to process.
- Clustering between JVMs doesn't scale - apps with large volumes of commits will quickly saturate the network with events, while most of those will be thrown away on the receiving end as mentioned above.
- Some contexts may not want to be refreshed. A refresh in the middle of an operation may lead to unpredictable results.
- Synchronization will interfere with optimistic locking.

So we've made a good case for disabling synchronization in most webapps. To do that, set to "false" the following DI property - `Constants.SERVER_CONTEXTS_SYNC_PROPERTY`, using one of the standard Cayenne DI approaches. E.g. from command line:

```
$ java -Dcayenne.server.contexts_sync_strategy=false
```

Or by changing the standard properties Map in a custom extensions module:

```
public class MyModule implements Module {

    @Override
    public void configure(Binder binder) {
        ServerModule.contributeProperties(binder)
            .put(Constants.SERVER_CONTEXTS_SYNC_PROPERTY, "false");
    }
}
```

2.9. Customizing Cayenne Runtime

Dependency Injection Container

Cayenne runtime is built around a small powerful dependency injection (DI) container. Just like other popular DI technologies, such as Spring or Guice, Cayenne DI container manages sets of interdependent objects and allows users to configure them. These objects are regular Java objects. We are calling them "services" in this document to distinguish from all other objects that are not configured in the container and are not managed. DI container is responsible for service instantiation, injecting correct dependencies, maintaining service instances scope, and dispatching scope events to services.

The services are configured in special Java classes called "modules". Each module defines binding of service interfaces to implementation instances, implementation types or providers of implementation instances. There are no XML configuration files, and all the bindings are type-safe. The container supports injection into instance variables and constructor parameters based on the `@Inject` annotation. This mechanism is very close to Google Guice.

The discussion later in this chapter demonstrates a standalone DI container. But keep in mind that Cayenne already has a built-in Injector, and a set of default modules. A Cayenne user would normally only use the API below to write custom extension modules that will be loaded in that existing container when creating `ServerRuntime`. See "Starting and Stopping `ServerRuntime`" chapter for an example of passing an extension module to Cayenne.

Cayenne DI probably has ~80% of the features expected in a DI container and has no dependency on the rest of Cayenne, so in theory can be used as an application-wide DI engine. But its primary purpose is still to serve Cayenne. Hence there are no plans to expand it beyond Cayenne needs. It is an ideal "embedded" DI that does not interfere with Spring, Guice or any other such framework present elsewhere in the application.

DI Bindings API

To have a working DI container, we need three things: service interfaces and classes, a module that describes service bindings, a container that loads the module, and resolves the dependencies. Let's start with service interfaces and classes:

```
public interface Service1 {  
    public String getString();  
}
```

```
public interface Service2 {  
    public int getInt();  
}
```

A service implementation using instance variable injection:

```
public class Service1Impl implements Service1 {  
    @Inject  
    private Service2 service2;  
  
    public String getString() {  
        return service2.getInt() + "_Service1Impl";  
    }  
}
```

Same thing, but using constructor injection:

```
public class Service1Impl implements Service1 {  
  
    private Service2 service2;  
  
    public Service1Impl(@Inject Service2 service2) {  
        this.service2 = service2;  
    }  
  
    public String getString() {  
        return service2.getInt() + "_Service1Impl";  
    }  
}
```

```
public class Service2Impl implements Service2 {  
    private int i;  
  
    public int getInt() {  
        return i++;  
    }  
}
```

Now let's create a module implementing `org.apache.cayenne.tutorial.di.Module` interface that will contain DI configuration. A module binds service objects to keys that are reference. Binder

provided by container implements fluent API to connect the key to implementation, and to configure various binding options (the options, such as scope, are demonstrated later in this chapter). The simplest form of a key is a Java Class object representing service interface. Here is a module that binds Service1 and Service2 to corresponding default implementations:

```
public class Module1 implements Module {  
  
    public void configure(Binder binder) {  
        binder.bind(Service1.class).to(Service1Impl.class);  
        binder.bind(Service2.class).to(Service2Impl.class);  
    }  
}
```

Once we have at least one module, we can create a DI container. `org.apache.cayenne.di.Injector` is the container class in Cayenne:

```
Injector injector = DIBootstrap.createInjector(new Module1());
```

Now that we have created the container, we can obtain services from it and call their methods:

```
Service1 s1 = injector.getInstance(Service1.class);  
for (int i = 0; i < 5; i++) {  
    System.out.println("S1 String: " + s1.getString());  
}
```

This outputs the following lines, demonstrating that s1 was Service1Impl and Service2 injected into it was Service2Impl:

```
0_Service1Impl  
1_Service1Impl  
2_Service1Impl  
3_Service1Impl  
4_Service1Impl
```

There are more flavors of bindings:

```
// binding to instance - allowing user to create and configure instance
// inside the module class
binder.bind(Service2.class).toInstance(new Service2Impl());

// binding to provider - delegating instance creation to a special
// provider class
binder.bind(Service1.class).toProvider(Service1Provider.class);

// binding to provider instance
binder.bind(Service1.class).toProviderInstance(new Service1Provider());

// multiple bindings of the same type using Key
// injection can reference the key name in annotation:
// @Inject("i1")
// private Service2 service2;
binder.bind(Key.get(Service2.class, "i1")).to(Service2Impl.class);
binder.bind(Key.get(Service2.class, "i2")).to(Service2Impl.class);
```

Another types of configuration that can be bound in the container are lists and maps. They will be discussed in the following chapters.

Service Lifecycle

An important feature of the Cayenne DI container is instance scope. The default scope (implicitly used in all examples above) is "singleton", meaning that a binding would result in creation of only one service instance, that will be repeatedly returned from `Injector.getInstance(..)`, as well as injected into classes that declare it as a dependency.

Singleton scope dispatches a "BeforeScopeEnd" event to interested services. This event occurs before the scope is shutdown, i.e. when `Injector.shutdown()` is called. Note that the built-in Cayenne injector is shutdown behind the scenes when `ServerRuntime.shutdown()` is invoked. Services may register as listeners for this event by annotating a no-argument method with `@BeforeScopeEnd` annotation. Such method should be implemented if a service needs to clean up some resources, stop threads, etc.

Another useful scope is "no scope", meaning that every time a container is asked to provide a service instance for a given key, a new instance will be created and returned:

```
binder.bind(Service2.class).to(Service2Impl.class).withoutScope();
```

Users can also create their own scopes, e.g. a web application request scope or a session scope. Most often than not custom scopes can be created as instances of `org.apache.cayenne.di.spi.DefaultScope` with startup and shutdown managed by the application (e.g. singleton scope is a `DefaultScope` managed by the Injector).

Overriding Services

Cayenne DI allows to override services already defined in the current module, or more commonly -

some other module in the the same container. Actually there's no special API to override a service, you'd just bind the service key again with a new implementation or provider. The last binding for a key takes precedence. This means that the order of modules is important when configuring a container. The built-in Cayenne injector ensures that Cayenne standard modules are loaded first, followed by optional user extension modules. This way the application can override the standard services in Cayenne.

Customization Strategies

The previous section discussed how Cayenne DI works in general terms. Since Cayenne users will mostly be dealing with an existing Injector provided by `ServerRuntime`, it is important to understand how to build custom extensions to a preconfigured container. As shown in "Starting and Stopping `ServerRuntime`" chapter, custom extensions are done by writing an application DI module (or multiple modules) that configures service overrides. This section shows all the configuration possibilities in detail, including changing properties of the existing services, contributing services to standard service lists and maps, and overriding service implementations. All the code examples later in this section are assumed to be placed in an application module "configure" method:

```
public class MyExtensionsModule implements Module {
    public void configure(Binder binder) {
        // customizations go here...
    }
}
```

```
Module extensions = new MyExtensionsModule();
ServerRuntime runtime = ServerRuntime.builder()
    .addConfig("com/example/cayenne-mydomain.xml")
    .addModule(extensions)
    .build();
```

Changing Properties of Existing Services

Many built-in Cayenne services change their behavior based on a value of some environment property. A user may change Cayenne behavior without even knowing which services are responsible for it, but setting a specific value of a known property. Supported property names are listed in "Appendix A".

There are two ways to set service properties. The most obvious one is to pass it to the JVM with `-D` flag on startup. E.g.

```
$ java -Dcayenne.server.contexts_sync_strategy=false ...
```

A second one is to contribute a property to `o.a.c.configuration.DefaultRuntimeProperties.properties` map (see the next section on how to do that). This map contains the default property values and can accept application-specific values,

overriding the defaults.

Note that if a property value is a name of a Java class, when this Java class is instantiated by Cayenne, the container performs injection of instance variables. So even the dynamically specified Java classes can use `@Inject` annotation to get a hold of other Cayenne services.

If the same property is specified both in the command line and in the properties map, the command-line value takes precedence. The map value will be ignored. This way Cayenne runtime can be reconfigured during deployment.

Contributing to Service Collections

Cayenne can be extended by adding custom objects to named maps or lists bound in DI. We are calling these lists/maps "service collections". A service collection allows things like appending a custom strategy to a list of built-in strategies. E.g. an application that needs to install a custom `DbAdapter` for some database type may contribute an instance of custom `DbAdapterDetector` to a `o.a.c.configuration.server.DefaultDbAdapterFactory.detectors` list:

```
public class MyDbAdapterDetector implements DbAdapterDetector {
    public DbAdapter createAdapter(DatabaseMetaData md) throws SQLException {
        // check if we support this database and return custom adapter
        ...
    }
}
```

```
ServerModule.contributeAdapterDetectors(binder)
    .add(MyDbAdapterDetector.class);
```

The names of built-in collections are listed in "Appendix B".

Alternative Service Implementations

As mentioned above, custom modules are loaded by `ServerRuntime` after the built-in modules. So it is easy to redefine a built-in service in Cayenne by rebinding desired implementations or providers. To do that, first we need to know what those services to redefine are. While we describe some of them in the following sections, the best way to get a full list is to check the source code of the Cayenne version you are using and namely look in `org.apache.cayenne.configuration.server.ServerModule` - the main built-in module in Cayenne.

Now an example of overriding `JdbcEventLogger` service. The default implementation of this service is provided by `Slf4jJdbcEventLogger`. But if we want to use `FormattedSlf4jJdbcEventLogger` (a logger with basic SQL formatting), we can define it like this:

```
binder.bind(JdbcEventLogger.class)
    .to(FormattedSlf4jJdbcEventLogger.class);
```

Using custom data types

Value object type

`ValueObjectType` is a new and lightweight alternative to the Extended Types API described in the following section. In most cases it should be preferred as it is easier to understand and use. Currently only one case is known when `ExtendedType` should be used: when your value object can be mapped on different JDBC types.

In order to use your custom data type you should implement `ValueObjectType` describing it in terms of some type already known to Cayenne (e.g. backed by system or user `ExtendedType`). Let's assume we want to support some data type called `Money`:

```
public class Money {
    private BigDecimal value;

    public Money(BigDecimal value) {
        this.value = value;
    }

    public BigDecimal getValue() {
        return value;
    }

    // .. some other business logic ..
}
```

Here is how `ValueObjectType` that will allow to store our `Money` class as `BigDecimal` can be implemented:

```

public class MoneyValueType implements ValueObjectType<Money, BigDecimal> {

    @Override
    public Class<BigDecimal> getTargetType() {
        return BigDecimal.class;
    }

    @Override
    public Class<Money> getValueType() {
        return Money.class;
    }

    @Override
    public Money toJavaObject(BigDecimal value) {
        return new Money(value);
    }

    @Override
    public BigDecimal fromJavaObject(Money object) {
        return object.getValue();
    }

    @Override
    public String toCacheKey(Money object) {
        return object.getValue().toString();
    }
}

```

Last step is to register this new type in `ServerRuntime`:

```

ServerRuntime runtime = ServerRuntime.builder()
    .addConfig("cayenne-project.xml")
    .addModule(binder ->
        ServerModule.contributeValueObjectTypes(binder)
            .add(MoneyValueType.class))
    .build();

```

More examples of implementation you can find in [cayenne-server](#).

Extended Types

JDBC specification defines a set of "standard" database column types (defined in `java.sql.Types` class) and a very specific mapping of these types to Java Object Types, such as `java.lang.String`, `java.math.BigDecimal`, etc. Sometimes there is a need to use a custom Java type not known to JDBC driver and Cayenne allows to configure it. For this Cayenne needs to know how to instantiate this type from a database "primitive" value, and conversely, how to transform an object of the custom type to a JDBC-compatible object.

Supporting Non-Standard Types

For supporting non-standard type you should define it via an interface `org.apache.cayenne.access.types.ExtendedType`. An implementation must provide `ExtendedType.getClassName()` method that returns a fully qualified Java class name for the supported custom type, and a number of methods that convert data between JDBC and custom type. The following example demonstrates how to add a custom `DoubleArrayType` to store `java.lang.Double[]` as a custom string in a database:

```
/**
 * Defines methods to read Java objects from JDBC ResultSets and write as parameters of
 * PreparedStatements.
 */
public class DoubleArrayType implements ExtendedType {

    private final String SEPARATOR = ",";

    /**
     * Returns a full name of Java class that this ExtendedType supports.
     */
    @Override
    public String getClassName() {
        return Double[].class.getCanonicalName();
    }

    /**
     * Initializes a single parameter of a PreparedStatement with object value.
     */
    @Override
    public void setJdbcObject(PreparedStatement statement, Object value,
        int pos, int type, int scale) throws Exception {

        String str = StringUtils.join((Double[]) value, SEPARATOR);
        statement.setString(pos, str);
    }

    /**
     * Reads an object from JDBC ResultSet column, converting it to class returned by
     * 'getClassName' method.
     *
     * @throws Exception if read error occurred, or an object can't be converted to a
     * target Java class.
     */
    @Override
    public Object materializeObject(ResultSet rs, int index, int type) throws
Exception {
        String[] str = rs.getString(index).split(SEPARATOR);
        Double[] res = new Double[str.length];
    }
```

```

        for (int i = 0; i < str.length; i++) {
            res[i] = Double.valueOf(str[i]);
        }

        return res;
    }

    /**
     * Reads an object from a stored procedure OUT parameter, converting it to class
     * returned by 'getClassName' method.
     *
     * @throws Exception if read error occurred, or an object can't be converted to a
     *         target Java class.
     */
    @Override
    public Object materializeObject(CallableStatement rs, int index, int type) throws
Exception {
        String[] str = rs.getString(index).split(SEPARATOR);
        Double[] res = new Double[str.length];

        for (int i = 0; i < str.length; i++) {
            res[i] = Double.valueOf(str[i]);
        }

        return res;
    }
}

```

For Java7

```

// add DoubleArrayType to list of user types
ServerRuntime runtime = ServerRuntime.builder()
    .addConfig("cayenne-project.xml")
    .addModule(new Module() {
        @Override
        public void configure(Binder binder) {
            ServerModule.contributeUserTypes(binder).add(new
DoubleArrayType());
        }
    })
    .build();

```

For Java8

```
// add DoubleArrayType to list of user types
ServerRuntime runtime = ServerRuntime.builder()
    .addConfig("cayenne-project.xml")
    .addModule(binder ->
        ServerModule.contributeUserTypes(binder)
            .add(new DoubleArrayType()))
    .build();
```

DbAdapters and Extended Types

As shown in the example above, ExtendedTypes are stored by DbAdapter. In fact DbAdapters often install their own extended types to address incompatibilities, incompleteness and differences between JDBC drivers in handling "standard" JDBC types. For instance some drivers support reading large character columns (CLOB) as `java.sql.Clob`, but some other - as "character stream", etc. Adapters provided with Cayenne override `configureExtendedTypes()` method to install their own types, possibly substituting Cayenne defaults. Custom DbAdapters can use the same technique.

Noteworthy Built-in Services

JdbcEventLogger

`org.apache.cayenne.log.JdbcEventLogger` is the service that defines logging API for Cayenne internals. It provides facilities for logging queries, commits, transactions, etc. The default implementation is `org.apache.cayenne.log.Slf4jJdbcEventLogger` that performs logging via slf4j-api library. Cayenne library includes another potentially useful logger - `org.apache.cayenne.log.FormattedSlf4jJdbcEventLogger` that produces formatted multiline SQL output that can be easier to read.

DataSourceFactory

Factory that returns `javax.sql.DataSource` object based on the configuration provided in the "nodeDescriptor".

DataChannelFilter

An interface of a filter that allows to intercept DataChannel operations. Filters allow to implement chains of custom processors around a DataChannel, that can be used for security, monitoring, business logic, providing context to lifecycle event listeners, etc.

QueryCache


Defines API of a cache that stores query results.

Chapter 3. Cayenne Framework - Remote Object Persistence

3.1. Introduction to ROP

What is ROP

"Remote Object Persistence" is a low-overhead web services-based technology that provides lightweight object persistence and query functionality to 'remote' applications. In other words it provides familiar Cayenne API to applications that do not have direct access to the database. Instead such applications would access Cayenne Web Service (CWS). A single abstract data model (expressed as Cayenne XML DataMap) is used on the server and on the client, while execution logic can be partitioned between the tiers. The following picture compares a regular Cayenne web application and a rich client application that uses remote object persistence technology:



Persistence stack above consists of the following parts:

- ORM Tier: a server-side Cayenne Java application that directly connects to the database via JDBC.
- CWS (Cayenne Web Service): A wrapper around an ORM tier that makes it accessible to remote CWS clients.

- Remote Tier (aka Client Tier): A Java application that has no direct DB connection and persists its objects by connecting to remote Cayenne Web Service (CWS). Note that CWS Client doesn't have to be a desktop application. It can be another server-side application. The word "client" means a client of Cayenne Web Service.

Main Features

- Unified approach to lightweight object persistence across multiple tiers of a distributed system.
- Same abstract object model on the server and on the client.
- Client can "bootstrap" from the server by dynamically loading persistence metadata.
- An ability to define client objects differently than the server ones, and still have seamless persistence.
- Generic web service interface that doesn't change when object model changes.
- An ability to work in two modes: dedicated session mode or shared ("chat") mode when multiple remote clients collaboratively work on the same data.
- Lazy object and collection faulting.
- Full context lifecycle
- Queries, expressions, local query caching, paginated queries.
- Validation
- Delete Rules

3.2. ROP Deployment

Server Security Note

Recent versions of Tomcat and Jetty containers (e.g. Tomcat 6 and 7, Jetty 8) contain code addressing a security concern related to "session fixation problem" by resetting the existing session ID of any request that requires BASIC authentication. If ROP service is protected with declarative security (see the ROP tutorial and the following chapters on security), this feature prevents the ROP client from attaching to its session, resulting in `MissingSessionExceptions`.

To solve that you will need to either switch to an alternative security mechanism, or disable "session fixation problem" protections of the container. E.g. the later can be achieved in Tomcat 7 by adding the following `context.xml` file to the webapp's `META-INF/` directory:

```
<Context>
  <Valve className="org.apache.catalina.authenticator.BasicAuthenticator"
        changeSessionIdOnAuthentication="false" />
</Context>
```

(The `<Valve>` tag can also be placed within the `<Context>` in any other locations used by Tomcat to load context configurations)

Chapter 4. DB-First Flow

4.1. Introduction

"DB-first" Flow

An ORM system consists of three parts: database, OR mapping and persistent Java classes. These parts always need to be kept in sync with each other for the application to work. "DB-first" flow is a common and practical approach to synchronization that assumes the database to be the master source of the metadata, with other two parts synchronized from the DB as the schema evolves. Cayenne provides a number of tools to automate and control it. Here is how "DB-first" flow is typically implemented:

- A SQL migrations framework is used to bring a local DB to a certain version. This is outside of the scope of Cayenne and is done with a third-party tool, such as Liquibase or Flyway.
- OR mapping model (Cayenne XML files) are synchronized with the state of the database using `"cdbimport"` tool provided by Cayenne.
- Object layer of the OR mapping model is customized to the developer liking, usually via CayenneModeler. Subsequent runs of `"cdbimport"` will not override any customizations that you make.
- Java classes are generated using `"cgen"` tool provided by Cayenne.

"cgen" and "cdbimport" tools can be invoked from Maven or Ant as discussed in the "Including Cayenne in a Project" chapter or run from CayenneModeler. This chapter will mostly focus on "cdbimport".

Here is simple maven configuration to start with:

Introduction to "cdbimport"

Here is a simple Maven configuration of "cdbimport" (for details see [cayenne-maven-plugin](#) documentation)

```

<plugin>
  <groupId>org.apache.cayenne.plugins</groupId>
  <artifactId>cayenne-maven-plugin</artifactId>
  <version>4.0.RC1</version>

  <configuration>
    <map>${project.basedir}/src/main/resources/datamap.map.xml</map>
    <dataSource>
      <url><!-- jdbc url --></url>
      <driver><!-- jdbc driver class --></driver>
      <username>username</username>
      <password>password</password>
    </dataSource>
    <dbimport>
      <defaultPackage>com.example.package</defaultPackage>
      <includeTable>.*</includeTable>
    </dbimport>
  </configuration>
  <dependencies>
    <!-- jdbc driver dependency -->
  </dependencies>
</plugin>

```

In the next chapters we will discuss various filtering and other reverse-engineering options.

4.2. Filtering

The first thing you usually want to control during reverse engineering is what exactly should be loaded from database and what not. One of the most common cases is excluding system tables, as you usually don't want to map them.

Briefly, you are able to include/exclude tables, columns and procedures and do it at several levels: default, catalog, schema. Although everything defined at the top level (default rules) will be applied for the nested elements, all rules from the most specific areas will override general rules (i.e. rules from schemas override rules from catalogs and even more override default rules).

The following use-cases will provide you a better understanding of how filtering works and how you could use it.

Process everything from schema/catalog

The simplest example of reverse engineering is processing tables from one schema of catalog and there are several options to do this. Basic syntax is described below:

```

<dbimport>
  <!-- Ant/Maven in case you only want to specify the schema to import -->
  <schema>SCHEMA_NAME</schema>

  <!-- Maven way in case you have nested elements in the schema -->
  <schema>
    <name>SCHEMA_NAME</name>
    ...
  </schema>

  <!-- Ant way in case you have nested elements in the schema -->
  <schema name="SCHEMA_NAME">
    ...
  </schema>
</dbimport>

```

The same options are available for catalogs:

```

<dbimport>
  <!-- Ant/Maven in case you only want to specify the catalog to import -->
  <catalog>CATALOG_NAME</catalog>

  <!-- Maven way in case you have nested elements in the catalog -->
  <catalog>
    <name>CATALOG_NAME</name>
    ...
  </catalog>

  <!-- Ant way in case you have nested elements in the catalog -->
  <catalog name="CATALOG_NAME">
    ...
  </catalog>
</dbimport>

```

Note

Current version of reverse engineering doesn't support catalog filtering for Postgres database.

Combine Schema and Catalog filters

Cayenne supports combination of different schemas and catalogs, and it filters data according to your requirements. You could achieve this by the following example of reverse engineering configuration:

```

<dbimport>

  <catalog>
    <name>shop_01</name>
    <schema>schema-name-01</schema>
    <schema>schema-name-02</schema>
    <schema>schema-name-03</schema>
  </catalog>

  <catalog>
    <name>shop_02</name>
    <schema>schema-name-01</schema>
  </catalog>

  <catalog>
    <name>shop_03</name>
    <schema>schema-name-01</schema>
    <schema>schema-name-02</schema>
    <schema>schema-name-03</schema>
  </catalog>

</dbimport>

```

In the example above, Cayenne reverse engineering process contains three catalogs named as shop_01, shop_02 and shop_03, each of which has their own schemas. Cayenne will load all data only from the declared catalogs and schemas.

If you want to load everything from database, you could simply declare catalog specification alone.

```

<dbimport>

  <catalog>shop_01</catalog>
  <catalog>shop_02</catalog>
  <catalog>shop_03</catalog>

</dbimport>

```

If you want to do reverse engineering for specific schemas, just remove unwanted schemas from the catalog section. For example, if you want to process schema-name-01 and schema-name-03 schemas only, then you should change reverse engineering section like this.

```

<dbimport>

  <catalog>
    <name>shop_01</name>
    <schema>schema-name-01</schema>
    <schema>schema-name-03</schema>
  </catalog>

  <catalog>
    <name>shop_02</name>
    <schema>schema-name-01</schema>
  </catalog>

  <catalog>
    <name>shop_03</name>
    <schema>schema-name-01</schema>
    <schema>schema-name-03</schema>
  </catalog>

</dbimport>

```

Including and Excluding tables, columns and procedures

Cayenne reverse engineering let you fine tune table, columns and stored procedures names that you need to import to your model file. In every filter you can use regexp syntax. Here is some examples of configuration for common tasks.

1) Include tables with 'CRM_' prefix if you are working in that domain of application:

```
<includeTable>CRM_.*</includeTable>
```

2) Include tables with '_LOOKUP' suffix

```

<includeTable>
  <pattern>.*_LOOKUP</pattern>
</includeTable>

```

3) Exclude tables with 'CRM_' prefix if you are not working only in that domain of application:

```
<excludeTable>CRM_.*</excludeTable>
```

4) Include only specific columns that follows specific naming convention:

```
<includeColumn>includeColumn01</includeColumn>
<includeColumn>includeColumn03</includeColumn>
```

5) Exclude system or obsolete columns:

```
<excludeColumn>excludeColumn01</excludeColumn>
<excludeColumn>excludeColumn03</excludeColumn>
```

6) Include/Exclude columns for particular table or group of tables:

```
<includeTable>
  <pattern>table pattern</pattern>
  <includeColumn>includeColumn01</includeColumn>
  <excludeColumn>excludeColumn01</excludeColumn>
</includeTable>
```

7) Include stored procedures:

```
<includeProcedure>includeProcedure01</includeProcedure>
<includeProcedure>
  <pattern>includeProcedure03</pattern>
</includeProcedure>
```

8) Exclude stored procedures by pattern:

```
<excludeProcedure>excludeProcedure01</excludeProcedure>
<excludeProcedure>
  <pattern>excludeProcedure03</pattern>
</excludeProcedure>
```

All filtering tags `<includeTable>`, `<excludeTable>`, `<includeColumn>`, `<excludeColumn>`, `<includeProcedure>` and `<excludeProcedure>` have 2 ways to pass filtering RegExp.

1) text inside tag

```
<includeTable>CRM_.*</includeTable>
```

2) pattern inner tag

```
<includeTable>
  <pattern>.*_LOOKUP</pattern>
</includeTable>
```

All filtering tags can be placed inside schema and catalog tags, but also inside `<dbimport>` tag. It means that filtering rules will be applied for all schemas and catalogs.

Complete filtering example

Initially, let's make a small sample. Consider the following reverse engineering configuration.

```
<dbimport>
  <catalog>shop-01</catalog>
</dbimport>
```

In this case reverse engineering will not filter anything from the shop-01 catalog. If you really want to filter database columns, tables, stored procedures and relationships, you could do it in the following way.

```
<dbimport>
  <catalog>shop-01</catalog>
  <catalog>
    <name>shop-02</name>
    <includeTable>includeTable-01</includeTable>
  </catalog>
</dbimport>
```

Then Cayenne will do reverse engineering for both shop-01 and shop-02 catalogs. First catalog will not be processed for filtering, but the second catalog will be processed with “includeTable-01” filter.

Let's assume you have a lot of table prefixes with the same names. Cayenne allows you to mention a pattern as regular expression. Using regular expressions is easier way to handle a big amount of database entities than writing filter config for each use-case. They make your configuration more readable, understandable and straightforward. There is not complex. Let's see how to use patterns in reverse engineering configuration with complete example.

```
<dbimport>

  <catalog>shop-01</catalog>

  <catalog>
    <name>shop-02</name>
  </catalog>

  <catalog>
    <name>shop-03</name>
    <includeTable>includeTable-01</includeTable>

    <includeTable>
      <pattern>includeTable-02</pattern>
    </includeTable>
  </catalog>
</dbimport>
```

```

<includeTable>
  <pattern>includeTable-03</pattern>
  <includeColumn>includeColumn-01</includeColumn>
  <excludeColumn>excludeColumn-01</excludeColumn>
</includeTable>

<excludeTable>excludeTable-01</excludeTable>

<excludeTable>
  <pattern>excludeTable-02</pattern>
</excludeTable>

<includeColumn>includeColumn-01</includeColumn>

<includeColumn>
  <pattern>includeColumn-02</pattern>
</includeColumn>

<excludeColumn>excludeColumn-01</excludeColumn>

<excludeColumn>
  <pattern>excludeColumn-02</pattern>
</excludeColumn>

<includeProcedure>includeProcedure-01</includeProcedure>

<includeProcedure>
  <pattern>includeProcedure-02</pattern>
</includeProcedure>

<excludeProcedure>excludeProcedure-01</excludeProcedure>

<excludeProcedure>
  <pattern>excludeProcedure-02</pattern>
</excludeProcedure>

</catalog>
</dbimport>

```

The example above should provide you more idea about how to use filtering and patterns in Cayenne reverse engineering. You could notice that this example demonstrates you the "name" and "pattern" configurations. Yes, you could use these as separates xml element and xml attributes.

The cdbimport will execute reverse engineering task for all entities from “shop-01” and “shop-02”, including tables, views, stored procedures and table columns. As “shop-03” has variety filter tags, entities from this catalog will be filtered by cdbimport.

Ant configuration example

Here is config sample for **Ant** task:

```
<!-- inside <cdbimport> tag -->
<catalog>shop-01</catalog>

<catalog name="shop-02"/>

<catalog name="shop-03">

    <includeTable>includeTable-01</includeTable>
    <includeTable pattern="includeTable-02"/>

    <includeTable pattern="includeTable-03">
        <includeColumn>includeColumn-01</includeColumn>
        <excludeColumn>excludeColumn-01</excludeColumn>
    </includeTable>

    <excludeTable>excludeTable-01</excludeTable>
    <excludeTable pattern="excludeTable-02"/>

    <includeColumn>includeColumn-01</includeColumn>
    <includeColumn pattern="includeColumn-02"/>

    <excludeColumn>excludeColumn-01</excludeColumn>
    <excludeColumn pattern="excludeColumn-02"/>

    <includeProcedure>includeProcedure-01</includeProcedure>
    <includeProcedure pattern="includeProcedure-02"/>

    <excludeProcedure>excludeProcedure-01</excludeProcedure>
    <excludeProcedure pattern="excludeProcedure-02"/>

</catalog>
```



In Ant task configuration all filter tags located inside root tag `<cdbimport>` as there is no `<dbimport>` tag.

4.3. Other Settings

In databases relations are defined via foreign keys and there are a lot of different politics according to the level of relationships and ways how those relationships could be modeled in database. Anyway, cdbimport is able to recognize basic patterns of relationships, such as OneToMany, OneToOne and ManyToMany.

Skip Relationships Loading

You are able to skip relationships loading by the `<skipRelationshipsLoading>` element.

```
<dbimport>
  <skipRelationshipsLoading>true</skipRelationshipsLoading>
</dbimport>
```

Skip Primary Keys Loading

Another useful Cayenne reverse engineering property is `<skipPrimaryKeyLoading>`. If you decide to support all relationships at the application layer and avoid their management in database, you'll find useful to turn off primary keys synchronization at all.

```
<dbimport>
  <skipPrimaryKeyLoading>true</skipPrimaryKeyLoading>
</dbimport>
```

Table Types

By default, `cdbimport` imports tables and views. Some databases may support other table-like objects, e.g. `SYSTEM TABLE`, `GLOBAL TEMPORARY`, `LOCAL TEMPORARY`, `ALIAS`, `SYNONYM`, etc. To control which types should be included `<tableType></tableType>` element is used. Some examples:

Import tables only (skip views and others and other types):

```
<dbimport>
  <tableType>TABLE</tableType>
</dbimport>
```

Tables and views (the default option):

```
<dbimport>
  <tableType>TABLE</tableType>
  <tableType>VIEWS</tableType>
</dbimport>
```


4.4. Reverse Engineering in Cayenne Modeler

Alternative approach to using `cdbimport` is doing reverse engineering from [CayenneModeler](#). Currently modeler GUI doesn't support all features of ant/maven tasks but it suffice for general DB import. Especially it's a good place to quickly start working on your data model.

You can find reverse engineering tool in main modeler menu **Tools > Reengineer Database Schema**

DataSource selection

First you should select DataSource. If you don't have any DataSource yet you can create one from this menu.




A screenshot of a macOS-style dialog box titled "Reengineer DB Schema: Connect to Database". It contains several input fields: "Saved DataSources:" with a dropdown menu showing "DataSource_MY" and a plus icon; "JDBC Driver:" with a text field containing "com.mysql.jdbc.Driver"; "DB URL:" with a text field containing "jdbc:mysql://localhost/"; "User Name:" with a text field containing "root"; "Password:" with a text field containing seven dots; and "Adapter (optional):" with a dropdown menu showing "org.apache.cayenne.dba.mysql.MySQLAdapter". At the bottom right are "Cancel" and "Continue" buttons.

Datasource selection dialog.

Reverse engineering options

Once DataSource is selected you can proceed to reverse engineering options.



A screenshot of a macOS-style dialog box titled "Reengineer DB Schema: Select Options". It contains several input fields: "Select Catalog:" with a dropdown menu showing "test"; "Table Name Include Pattern:" with a text field containing ".*"; "Table Name Exclude Pattern:" with an empty text field; "Procedure Name Pattern:" with a text field containing ".*"; "Naming Strategy:" with a dropdown menu showing "org.apache.cayenne.dbsync.naming.DefaultObjectNameGenerator"; "Tables with Meaningful PK Pattern:" with an empty text field; "Use Java primitive types:" with a checked checkbox; and "Use old java.util.Date type:" with an unchecked checkbox. At the bottom right are "Continue" and "Cancel" buttons.

Reverse Engineering dialog.

Here is a list of options to tune what will be processed by reverse engineering:

- **Select Catalog:** catalog to process



You can only select one catalog. If you need to import multiple catalogs you need to run process several times.

- **Table Name Pattern:** RegExp to filter tables. Default pattern `.*` includes all tables.
- **Procedure Name Pattern:** RegExp to filter procedures. Default pattern `.*` includes all stored procedures.
- **Naming Strategy:** Currently there is only one naming strategy available. See [ant/maven tools documentation](#) for details about naming strategy.
- **Tables with Meaningful PK Pattern:** Comma separated list of RegExp's for tables that you want to have meaningful primary keys. By default no meaningful PKs are created.
- **Use Java primitive types:** Use primitive types (e.g. `int`) or Object types (e.g. `java.lang.Integer`).
- **Use old `java.util.Date` type:** Use `java.util.Date` for all columns with `DATE/TIME/TIMESTAMP` types. By default `java.time` types will be used.

Chapter 5. Cayenne Additional Modules

5.1. Cache invalidation extension

Description

Cache invalidation module is an extension that allows to define cache invalidation policy programmatically.

Including in a project

Maven

```
<dependency>
  <groupId>org.apache.cayenne</groupId>
  <artifactId>cayenne-cache-invalidation</artifactId>
  <version>4.0.RC1</version>
</dependency>
```

Gradle

```
compile 'org.apache.cayenne:cayenne-cache-invalidation:4.0.RC1'
```

Usage

Module supports autoloading mechanism, so no other actions required to enable it. Just mark your entities with `@CacheGroups` annotation and you are ready to use it:

```
@CacheGroups("some-group")
public class MyEntity extends _MyEntity {
    // ...
}
```

After any modification of `MyEntity` objects cache group `"some-group"` will be dropped from cache automatically.

Note

You can read more about cache and cache groups in corresponding [chapter](#) of this documentation.

In case you need some complex logic of cache invalidation you can disable default behaviour and provide your own.

To do so you need to implement `org.apache.cayenne.cache.invalidation.InvalidHandler` interface and setup Cache Invalidation module to use it. Let's use implementation class called

`CustomInvalidationHandler` that will simply match all entities' types with `"custom-group"` cache group regardless of any annotations:

```
public class CustomInvalidationHandler implements InvalidationHandler {
    @Override
    public InvalidationFunction canHandle(Class<? extends Persistent> type) {
        return p -> Collections.singleton(new CacheGroupDescriptor("custom-group"));
    }
}
```

Now we'll set up its usage by `ServerRuntime`:

```
ServerRuntime.builder()
    .addModule(CacheInvalidationModule.extend()
        // optionally you can disable @CacheGroups annotation processing
        .noCacheGroupsHandler()
        .addHandler(CustomInvalidationHandler.class)
        .module())
```



You can combine as many invalidation handlers as you need.

5.2. Commit log extension

Description

The goal of this module is to capture commit changes and present them to interested parties in an easy-to-process format.

Including in a project

Maven

```
<dependency>
  <groupId>org.apache.cayenne</groupId>
  <artifactId>cayenne-commitlog</artifactId>
  <version>4.0.RC1</version>
</dependency>
```

Gradle

```
compile 'org.apache.cayenne:cayenne-commitlog:4.0.RC1'
```

Usage

In order to use `commitlog` module you need to perform three steps:

1. Mark all entities which changes you are interested in with `@org.apache.cayenne.commitlog.CommitLog` annotation

```
@CommitLog(ignoredProperties = {"somePrivatePropertyToSkip"})
public class MyEntity extends _MyEntity {
    // ...
}
```

2. Implement `CommitLogListener` interface.

```
public class MyCommitLogListener implements CommitLogListener {
    @Override
    public void onPostCommit(ObjectContext originatingContext, ChangeMap changes) {
        // ChangeMap will contain all information about changes happened in
        // performed commit
        // this particular example will print IDs of all inserted objects
        changes.getUniqueChanges().stream()
            .filter(change -> change.getType() == ObjectChangeType.INSERT)
            .map(ObjectChange::getPostCommitId)
            .forEach(id -> System.out.println("Inserted new entity with id: " + id
    ));
}
```

3. Register your listener implementation.

```
ServerRuntime.builder()
    .addModule(CommitLogModule.extend()
        .addListener(MyCommitLogListener.class)
        .module())
```



You can use several listeners, but they all will get same changes.

5.3. Crypto extension

Description

Crypto module allows encrypt and decrypt values stored in DB transparently to your Java app.

Including in a project

Maven

```
<dependency>
  <groupId>org.apache.cayenne</groupId>
  <artifactId>cayenne-crypto</artifactId>
  <version>4.0.RC1</version>
</dependency>
```

Gradle

```
compile 'org.apache.cayenne:cayenne-crypto:4.0.RC1'
```

Usage

Setup your model and DB

To use crypto module you must prepare your database to allow `byte[]` storage and properly name columns that will contain encrypted values.

Currently supported SQL types that can be used to store encrypted data are:

1. Binary types: `BINARY`, `BLOB`, `VARBINARY`, `LONGVARBINARY`. These types are preferred.
2. Character types, that will store `base64` encoded value: `CHAR`, `NCHAR`, `CLOB`, `NCLOB`, `LONGVARCHAR`, `LONGNVARCHAR`, `VARCHAR`, `NVARCHAR`.

Note

Not all data types may be supported by your database.

Default naming strategy that doesn't require additional setup suggests using "CRYPTO_" prefix. You can change this default strategy by injecting your own implementation of `org.apache.cayenne.crypto.map.ColumnMapper` interface.

```
ServerRuntime.builder()
    .addModule(CryptoModule.extend()
        .columnMapper(MyColumnMapper.class)
        .module())
```

Here is an example of how `ObjEntity` with two encrypted and two unencrypted properties can look like:

Name ▾	Java Type	DbAttribute Path	DB Type
intField1	int	CRYPTO_INT_FIELD	BLOB
intField2	int	INT_FIELD	INTEGER
stringField1	java.lang.String	CRYPTO_STRING_FIELD	BLOB
stringField2	java.lang.String	STRING_FIELD	VARCHAR

Setup keystore

To perform encryption you must provide `KEYSTORE_URL` and `KEY_PASSWORD`. Currently crypto module supports only Java "jceks" KeyStore.

```
ServerRuntime.builder()
    .addModule(CryptoModule.extend()
        .keyStore(this.getClass().getResource("keystore.jcek"), "my-password"
        .toCharArray(), "my-key-alias")
        .module())
```

Additional settings

Additionally to `ColumnMapper` mentioned above you can customize other parts of `crypto module`. You can enable `gzip` compression and `HMAC` usage (later will ensure integrity of data).

```
ServerRuntime.builder()
    .addModule(CryptoModule.extend()
        .compress()
        .useHMAC()
        .module())
```

Another useful extension point is support for custom Java value types. To add support for your data type you need to implement `org.apache.cayenne.crypto.transformer.value.BytesConverter` interface that will convert required type to and from `byte[]`.

```
ServerRuntime.builder()
    .addModule(CryptoModule.extend()
        .objectToBytesConverter(MyClass.class, new MyClassBytesConverter())
        .module())
```



In addition to Java primitive types (and their object counterparts), `crypto module` supports encryption only of `java.util.Date`, `java.math.BigInteger` and `java.math.BigDecimal` types.

5.4. Apache Commons DBCP integration

Description

This module enables usage of Apache Commons DBCP2 connection pool.

Including in a project

Maven

```
<dependency>
  <groupId>org.apache.cayenne</groupId>
  <artifactId>cayenne-dbc2</artifactId>
  <version>4.0.RC1</version>
</dependency>
```

Gradle

```
compile 'org.apache.cayenne:cayenne-dbc2:4.0.RC1'
```

Usage

To use DBCP2 pool you need to setup it in DataNode settings in Cayenne Modeler:

DataNode Configuration

DataNode Name:

Schema Update Strategy:

You can enter custom class implementing SchemaUpdateStrategy

Local DataSource (opt.):

DataSource Factory:

Apache DBCP2 Configuration

DBCP2 Properties File:

5.5. Java 8 extension

Description

Java 8 module allows to use `java.time.LocalTime`, `java.time.LocalDate` and `java.time.LocalDateTime` types for entity attributes

Including in a project

Maven

```
<dependency>
  <groupId>org.apache.cayenne</groupId>
  <artifactId>cayenne-java8</artifactId>
  <version>4.0.RC1</version>
</dependency>
```

Gradle

```
compile 'org.apache.cayenne:cayenne-java8:4.0.RC1'
```

Usage

This module doesn't require any additional setup, you can just use new data types in your model.

5.6. JCache integration

Description

This module allows to integrate any JCache (JSR 107) compatible caching provider with Cayenne.

Including in a project

Maven

```
<dependency>
  <groupId>org.apache.cayenne</groupId>
  <artifactId>cayenne-jcache</artifactId>
  <version>4.0.RC1</version>
</dependency>
```

Gradle

```
compile 'org.apache.cayenne:cayenne-jcache:4.0.RC1'
```

Usage

To use JCache provider in your app you need to include this module and caching provider libs (e.g. Ehcache). You can provide own implementation of `org.apache.cayenne.jcache.JCacheConfigurationFactory` to customize cache configuration if required.

For advanced configuration and management please use provider specific options and tools.



You can read about using cache in Cayenne in [this](#) chapter.

You may also be interested in [Cache invalidation extension](#).

5.7. Joda time extension

Description

Joda time module allows to use `org.joda.time.LocalDateTime`, `org.joda.time.LocalDate`, `org.joda.time.LocalDateTime` and `org.joda.time.DateTime` types for entity attributes.

Including in a project

Maven

```
<dependency>
  <groupId>org.apache.cayenne</groupId>
  <artifactId>cayenne-joda</artifactId>
  <version>4.0.RC1</version>
</dependency>
```

Gradle

```
compile 'org.apache.cayenne:cayenne-joda:4.0.RC1'
```

Usage

This module doesn't require any additional setup, you can just use new data types in your model.

Chapter 6. Appendix A. Configuration Properties

Note that the property names below are defined as constants in `org.apache.cayenne.configuration.Constants` interface.

- `cayenne.jdbc.driver[.domain_name.node_name]` defines a JDBC driver class to use when creating a `DataSource`. If domain name and optionally - node name are specified, the setting overrides `DataSource` info just for this domain/node. Otherwise the override is applied to all domains/nodes in the system.
 - Default value: none, project `DataNode` configuration is used
- `cayenne.jdbc.url[.domain_name.node_name]` defines a DB URL to use when creating a `DataSource`. If domain name and optionally - node name are specified, the setting overrides `DataSource` info just for this domain/node. Otherwise the override is applied to all domains/nodes in the system.
 - Default value: none, project `DataNode` configuration is used
- `cayenne.jdbc.username[.domain_name.node_name]` defines a DB user name to use when creating a `DataSource`. If domain name and optionally - node name are specified, the setting overrides `DataSource` info just for this domain/node. Otherwise the override is applied to all domains/nodes in the system.
 - Possible values: any
 - Default value: none, project `DataNode` configuration is used
- `cayenne.jdbc.password[.domain_name.node_name]` defines a DB password to use when creating a `DataSource`. If domain name and optionally - node name are specified, the setting overrides `DataSource` info just for this domain/node. Otherwise the override is applied to all domains/nodes in the system.
 - Default value: none, project `DataNode` configuration is used
- `cayenne.jdbc.min_connections[.domain_name.node_name]` defines the DB connection pool minimal size. If domain name and optionally - node name are specified, the setting overrides `DataSource` info just for this domain/node. Otherwise the override is applied to all domains/nodes in the system.
 - Default value: none, project `DataNode` configuration is used
- `cayenne.jdbc.max_connections[.domain_name.node_name]` defines the DB connection pool maximum size. If domain name and optionally - node name are specified, the setting overrides `DataSource` info just for this domain/node. Otherwise the override is applied to all domains/nodes in the system.
 - Default value: none, project `DataNode` configuration is used
- `cayenne.querycache.size` An integer defining the maximum number of entries in the query cache. Note that not all `QueryCache` providers may respect this property. `MapQueryCache` uses it, but the rest would use alternative configuration methods.
 - Possible values: any positive int value
 - Default value: 2000

- `cayenne.server.contexts_sync_strategy` defines whether peer ObjectContexts should receive snapshot events after commits from other contexts. If true (*default*), the contexts would automatically synchronize their state with peers.
 - Possible values: true, false
 - Default value: true
- `cayenne.server.object_retain_strategy` defines fetched objects retain strategy for ObjectContexts. When weak or soft strategy is used, objects retained by ObjectContext that have no local changes can potentially get garbage collected when JVM feels like doing it.
 - Possible values: weak, soft, hard
 - Default value: weak
- `cayenne.server.max_id_qualifier_size` defines a maximum number of ID qualifiers in the WHERE clause of queries that are generated for paginated queries and for DISJOINT_BY_ID prefetch processing. This is needed to avoid hitting WHERE clause size limitations and memory usage efficiency.
 - Possible values: any positive int
 - Default value: 10000
- `cayenne.server.external_tx` defines whether runtime should use external transactions.
 - Possible values: true, false
 - Default value: false
- `cayenne.rop.service_url` defines the URL of the ROP server
 - Default value: none
- `cayenne.rop.service_username` defines the user name for an ROP client to login to an ROP server.
 - Default value: none
- `cayenne.rop.service_password` defines the password for an ROP client to login to an ROP server.
 - Default value: none
- `cayenne.rop.shared_session_name` defines the name of the shared session that an ROP client wants to join on an ROP server. If omitted, a dedicated session is created.
 - Default value: none
- `cayenne.rop.service.timeout` a value in milliseconds for the ROP client-server connection read operation timeout
 - Possible values: any positive long value
 - Default value: none
- `cayenne.rop.channel_events` defines whether client-side DataChannel should dispatch events to child ObjectContexts. If set to true, ObjectContexts will receive commit events and merge changes committed by peer contexts that passed through the common client DataChannel.
 - Possible values: true, false
 - Default value: false
- `cayenne.rop.context_change_events` defines whether object property changes in the client

context result in firing events. Client UI components can listen to these events and update the UI. Disabled by default.

- Possible values: true, false
- Default value: false
- `cayenne.rop.context_lifecycle_events` defines whether object commit and rollback operations in the client context result in firing events. Client UI components can listen to these events and update the UI. Disabled by default.
 - Possible values: true,false
 - Default value: false
- `cayenne.server.rop_event_bridge_factory` defines the name of the `org.apache.cayenne.event.EventBridgeFactory` that is passed from the ROP server to the client. I.e. server DI would provide a name of the factory, passing this name to the client via the wire. The client would instantiate it to receive events from the server. Note that this property is stored in `cayenne.server.rop_event_bridge_properties` map, not in the main `cayenne.properties`.
 - Default value: false

Chapter 7. Appendix B. Service Collections

Note that the collection keys below are defined as constants in `org.apache.cayenne.configuration.Constants` interface.

Table 13. Service Collection Keys Present in *ServerRuntime* and/or *ClientRuntime*

Collection Property	Type	Description
<code>cayenne.properties</code>	<code>Map<String,String></code>	Properties used by built-in Cayenne services. The keys in this map are the property names from the table in Appendix A. Separate copies of this map exist on the server and ROP client.
<code>cayenne.server.adapter_detectors</code>	<code>List<DbAdapterDetector></code>	Contains objects that can discover the type of current database and install the correct <code>DbAdapter</code> in runtime.
<code>cayenne.server.domain_filters</code>	<code>List<DataChannelFilter></code>	Stores <code>DataDomain</code> filters.
<code>cayenne.server.project_locations</code>	<code>List<String></code>	Stores locations of the one of more project configuration files.
<code>cayenne.server.default_types</code>	<code>List<ExtendedType></code>	Stores default adapter-agnostic <code>ExtendedTypes</code> . Default <code>ExtendedTypes</code> can be overridden / extended by DB-specific <code>DbAdapters</code> as well as by user-provided types configured in another collection (see " <code>cayenne.server.user_types</code> ").
<code>cayenne.server.user_types</code>	<code>List<ExtendedType></code>	Stores a user-provided <code>ExtendedTypes</code> . This collection will be merged into a full list of <code>ExtendedTypes</code> and would override any <code>ExtendedTypes</code> defined in a default list, or by a <code>DbAdapter</code> .
<code>cayenne.server.type_factories</code>	<code>List<ExtendedTypeFactory></code>	Stores default and user-provided <code>ExtendedTypeFactories</code> . <code>ExtendedTypeFactory</code> allows to define <code>ExtendedTypes</code> dynamically for the whole group of Java classes. E.g. Cayenne supplies a factory to map all Enums regardless of their type.

Collection Property	Type	Description
<code>cayenne.server.rop_event_bridge_properties</code>	<code>Map<String, String></code>	Stores event bridge properties passed to the ROP client on bootstrap. This means that the map is configured by server DI, and passed to the client via the wire. The properties in this map are specific to EventBridgeFactory implementation (e.g JMS or XMPP connection parameters). One common property is <code>"cayenne.server.rop_event_bridge_factory"</code> that defines the type of the factory.

Chapter 8. Appendix C. Expressions BNF

```
TOKENS
<DEFAULT> SKIP : {
  " "
  | "\t"
  | "\n"
  | "\r"
}

<DEFAULT> TOKEN : {
  <NULL: "null" | "NULL">
  | <TRUE: "true" | "TRUE">
  | <FALSE: "false" | "FALSE">
}

<DEFAULT> TOKEN : {
  <PROPERTY_PATH: <IDENTIFIER> ("." <IDENTIFIER>)*>
}

<DEFAULT> TOKEN : {
  <IDENTIFIER: <LETTER> (<LETTER> | <DIGIT>)* ([ "+" ])?>
  | <#LETTER: [ "_" , "a" - "z" , "A" - "Z" ]>
  | <#DIGIT: [ "0" - "9" ]>
}

/**
 * Quoted Strings, whose object value is stored in the token manager's
 * "literalValue" field. Both single and double quotes are allowed
 */
<DEFAULT> MORE : {
  "\"" : WithinSingleQuoteLiteral
  | "\"" : WithinDoubleQuoteLiteral
}

<WithinSingleQuoteLiteral> MORE : {
  <ESC: "\\" ([ "n" , "r" , "t" , "b" , "f" , "\"\" , "\"" , "\"" , "\"" ] | ([ "0" - "3" ])? [ "0" - "7" ] ([ "0" - "7" ])?)> : {
  | <~["\'", "\\"]> : {
  }

  <WithinSingleQuoteLiteral> TOKEN : {
  <SINGLE_QUOTED_STRING: "\"" : DEFAULT
  }

  <WithinDoubleQuoteLiteral> MORE : {
  <STRING_ESC: <ESC>> : {
  | <~["\"", "\\"]> : {
  }
```

```

<WithinDoubleQuotedLiteral> TOKEN : {
<DOUBLE_QUOTED_STRING: "\""> : DEFAULT
}

/**
 * Integer or real Numeric literal, whose object value is stored in the token
manager's
 * "literalValue" field.
 */<DEFAULT> TOKEN : {
<INT_LITERAL: ("0" (["0"-"7"])* | ["1"-"9"] (["0"-"9"])* | "0" ["x","X"] (["0"-"9",
"a"-"f","A"-"F"])+)
    (["l","L","h","H"])?> : {
| <FLOAT_LITERAL: <DEC_FLT> (<EXPONENT>)? (<FLT_SUFF>)? | <DEC_DIGITS> <EXPONENT>
(<FLT_SUFF>)?
| <DEC_DIGITS> <FLT_SUFF>> : {
| <#DEC_FLT: (["0"-"9"])+ "." (["0"-"9"])* | "." (["0"-"9"])+>
| <#DEC_DIGITS: (["0"-"9"])+>
| <#EXPONENT: ["e","E"] (["+", "-"])? (["0"-"9"])+>
| <#FLT_SUFF: ["d","D","f","F","b","B"]>
}
}

```

NON-TERMINALS

```

expression      :=    orCondition <EOF>
orCondition      :=    andCondition ( "or" andCondition )*
andCondition     :=    notCondition ( "and" notCondition )*
notCondition     :=    ( "not" | "!" ) simpleCondition
                    |    simpleCondition
simpleCondition   :=    <TRUE>
                    |    <FALSE>
                    |    scalarConditionExpression
                    ( simpleNotCondition
                      | ( "=" | "==" ) scalarExpression
                      | ( "!=" | "<>" ) scalarExpression
                      | "<=" scalarExpression
                      | "<" scalarExpression | ">" scalarExpression
                      | ">=" scalarExpression
                      | "like" scalarExpression
                      | "likeIgnoreCase" scalarExpression
                      | "in" ( namedParameter | "(" scalarCommaList ")" )
                      | "between" scalarExpression "and" scalarExpression
                    )?
simpleNotCondition :=    ( "not" | "!" )
                    ( "like" scalarExpression
                      | "likeIgnoreCase" scalarExpression
                      | "in" ( namedParameter | "(" scalarCommaList ")" )
                      | "between" scalarExpression "and" scalarExpression
                    )
scalarCommaList  :=    ( scalarConstExpression ( "," scalarConstExpression )* )
scalarConditionExpression :=    scalarNumericExpression
                    |    <SINGLE_QUOTED_STRING>
                    |    <DOUBLE_QUOTED_STRING>

```

```

| <NULL>
scalarExpression := scalarConditionExpression
| <TRUE>
| <FALSE>
scalarConstExpression := <SINGLE_QUOTED_STRING>
| <DOUBLE_QUOTED_STRING>
| namedParameter
| <INT_LITERAL>
| <FLOAT_LITERAL>
| <TRUE>
| <FALSE>
scalarNumericExpression := multiplySubtractExp
    ( "+" multiplySubtractExp | "-" multiplySubtractExp )*
multiplySubtractExp := numericTerm ( "*" numericTerm | "/" numericTerm )*
numericTerm := ( "+" )? numericPrimary
| "-" numericPrimary
numericPrimary := "(" orCondition ")"
| pathExpression
| namedParameter
| <INT_LITERAL>
| <FLOAT_LITERAL>
namedParameter := "$" <PROPERTY_PATH>
pathExpression := ( <PROPERTY_PATH>
| "obj:" <PROPERTY_PATH>
| "db:" <PROPERTY_PATH>
| "enum:" <PROPERTY_PATH> )

```

Chapter 9. List of tables

- [Cayenne Version History](#)
- [modeler plugin parameters](#)
- [cgen required parameters](#)
- [cgen optional parameters](#)
- [cdbgen required parameters](#)
- [<dataSource> parameters](#)
- [cdbgen optional parameters](#)
- [cdbimport parameters](#)
- [<dataSource> parameters](#)
- [<dbimport> parameters](#)
- [Persistence States](#)
- [Lifecycle Event Types](#)
- [Configuration Properties Recognized by ServerRuntime and/or ClientRuntime](#)
- [Service Collection Keys Present in ServerRuntime and/or ClientRuntime](#)